SWS HARDWARE

Tel: 01626 333900
Email: info@swshardware.com



# 19mm Safety Lever Handles - Push-On Rose - 52mm

**Variant code: 1035.19.02.SSS**

**19mm Safety Lever Handles** combine modern architectural styling with enhanced user safety and durability. Manufactured from **Grade 304 stainless steel**, these premium lever handles feature a **19mm diameter return-to-door lever** mounted on an elegant **52mm push-on sprung rose**. Designed for both commercial and residential applications, they provide smooth operation, excellent corrosion resistance and compliance with recognised accessibility and fire safety standards.

The return-to-door lever design helps minimise the risk of clothing or bags catching on the handle, making it particularly suitable for healthcare, education and public buildings. The integrated sprung rose supports smooth lever return after operation, while the concealed push-on fixing creates a clean, contemporary appearance. Certified to **BS EN 1906 Grade 3** and suitable for **FD30 and FD60 fire-rated doors**, these handles also comply with **BS8300 (DDA)** accessibility recommendations, making them ideal for inclusive building design.

Available in a choice of **Satin Stainless Steel (SSS) finish**, these safety lever handles provide a durable, low-maintenance solution for high-traffic environments where both appearance and performance are essential.

## Product Features

- 19mm diameter return-to-door safety lever handles
- 52mm push-on sprung rose with concealed fixings
- Manufactured from Grade 304 stainless steel
- Return-to-door design improves user safety
- Certified to BS EN 1906 Grade 3
- Suitable for FD30 and FD60 fire-rated doors
- Complies with BS8300 (DDA) accessibility guidance
- Available in Satin Stainless Steel (SSS)

## Product Benefits

Tel: 01626 333900
Email: info@swshardware.com

- **Return-to-door lever design helps reduce snagging and improves user safety**
- **Grade 304 stainless steel offers excellent durability and corrosion resistance**
- **Push-on sprung rose provides smooth operation with a concealed contemporary appearance**
- Suitable for high-traffic commercial and public buildings
- Supports accessible building design in accordance with BS8300
- Fire door compatible for FD30 and FD60 applications
- Low-maintenance finish suitable for demanding environments
- Professional architectural appearance for modern interiors

## Technical Characteristics

- Product Type: Lever Door Handles on Rose
- Lever Diameter: 19mm
- Rose Diameter: 52mm
- Rose Type: Push-On Sprung Rose
- Rose Thickness: 8mm
- Material: Grade 304 Stainless Steel
- Certification: BS EN 1906 Grade 3
- Fire Rating: FD30 / FD60
- Accessibility: BS8300 (DDA) Compliant
- Available Finish: Satin Stainless Steel

## Applications

The **19mm Safety Lever Handles Push-On Rose** are ideal for **schools, hospitals, healthcare facilities, offices, hotels, apartment buildings, public buildings, retail premises and commercial developments**. Suitable for installation on **timber and metal internal doors, including FD30 and FD60 fire doors**, they provide safe, accessible and reliable operation in environments where durability, compliance and contemporary design are essential.

| Property | Value |
| --- | --- |
| Finish | Satin Stainless Steel |
| Material | Grade 304 Stainless Steel |
| Fire Rating | Tested for FD30 & FD60 Timber Fire Doors (BS EN 1634-1) |

SWS HARDWARE

Tel: 01626 333900
Email: info@swshardware.com

| Property | Value |
| --- | --- |
| Door Thickness (mm) | Suitable for 35–54mm doors |
| Durability | 200,000 Cycle Tested |
| Lever Diameter (mm) | 19 |
| Rose Size | 52mm Diameter × 8mm Projection |
| Rose Type | Push-On Sprung Round Rose |
| Performance Standard | BS EN 1906:2010 Grade 3 |
| Corrosion Resistance | BS EN 1670 Grade 5 |