



19mm Straight T-Bar Lever Handles on 52mm Rose – Satin Stainless Steel

Variant code: 1194.19.02.SSS

19mm Straight T-Bar Lever Handles on 52mm Sprung Rose offer a clean, contemporary design combined with dependable everyday performance, making them ideal for commercial, residential and public buildings. Manufactured from **ZCS Grade 201 stainless steel** with a **Satin Stainless Steel (SSS)** finish, these straight T-bar lever handles provide a modern architectural appearance while delivering durability and corrosion resistance for interior door applications.

Mounted on a **52mm push-on sprung rose** with an **8mm projection**, the integrated spring mechanism ensures smooth lever return and reliable operation while reducing wear on the door latch. The concealed **push-on stainless steel outer rose** creates a seamless finish, while the handle set is supplied complete with a **100mm Heso steel spindle**, **M4 male/female bolt-through fixings**, **M6 Heso grub screws** for enhanced fixing strength, and **20mm wood screws** for secure installation. Suitable for **35–54mm thick doors**, these lever handles are **fire tested for use on 30 and 60-minute timber fire doors** and achieve **BS EN 1670 Grade 5** for corrosion resistance, ensuring reliable long-term performance.

Combining modern styling, concealed fixings and practical durability, these straight T-bar lever handles provide a cost-effective architectural hardware solution for a wide range of commercial and residential projects.

Product Features

- Contemporary **19mm straight T-bar tubular lever**
- **52mm diameter push-on sprung rose**
- **8mm rose projection**
- Manufactured from **ZCS Grade 201 stainless steel**
- **Satin Stainless Steel (SSS) finish**
- **Push-on stainless steel outer rose**
- Supplied with **100mm Heso steel spindle**
- **M4 male/female bolt-through fixings included**



- **M6 Heso grub screws** for additional fixing strength
- Includes **20mm wood screws**
- Suitable for **35–54mm door thickness**
- **Fire tested** for **30 & 60-minute timber fire doors**
- **BS EN 1670 Grade 5** corrosion tested

Product Benefits

- Contemporary straight T-bar design complements modern interiors
- Sprung rose ensures smooth and reliable lever return
- Grade 201 stainless steel provides dependable durability for everyday use
- Concealed push-on rose delivers a clean architectural appearance
- Heavy-duty fixings provide a secure, long-lasting installation
- Suitable for certified timber fire door applications
- Excellent corrosion resistance for extended service life
- Ideal for commercial, public and residential environments

Technical Characteristics

- **Product Type:** Straight T-Bar Lever Handle Set
- **Lever Diameter:** 19mm
- **Lever Style:** Straight T-Bar Tubular
- **Rose Diameter:** 52mm
- **Rose Projection:** 8mm
- **Rose Type:** Push-On Sprung Rose
- **Material:** ZCS Grade 201 Stainless Steel
- **Finish:** Satin Stainless Steel (SSS)
- **Door Thickness:** 35–54mm
- **Spindle:** 100mm Heso Steel
- **Fixings:** M4 Male/Female Bolts, M6 Heso Grub Screws, 20mm Wood Screws
- **Fire Rating:** Suitable for 30 & 60 Minute Timber Fire Doors
- **Corrosion Standard:** BS EN 1670 Grade 5

Applications

The **19mm Straight T-Bar Lever Handles on 52mm Sprung Rose** are ideal for **offices, schools, healthcare facilities, hotels, apartment developments, retail premises, public buildings and residential properties**. Suitable for **35–54mm internal timber and fire-rated doors**, they provide a durable and contemporary door hardware solution, combining **Grade 201 stainless**

steel construction, fire door compatibility, high corrosion resistance, and concealed push-on fixings with a premium **Satin Stainless Steel finish** for dependable long-term performance.

Property	Value
Finish	Satin Stainless Steel
Material	ZCS Grade 201 Stainless Steel
Fire Rating	Suitable for 30 & 60 Minute Timber Fire Doors
Rose Diameter (mm)	52
Door Thickness (mm)	35-54
Fixing Type	M4 Male/Female Bolts, M6 Heso Grub Screws, 20mm Wood Screws
Product Type	Straight T-Bar Lever Handle Set
Lever Diameter (mm)	19
Rose Type	Push-On Sprung Rose
Standards Tested	BS EN 1670 Grade 5
Rose Projection (mm)	8
Lever Style	Straight T-Bar Tubular
Spindle	100mm Heso Steel