




Blum Clip Top Hinge – 95° Blind Corner Overlay BLUMOTION Sprung – Nickel – Screw-on

Variant code: 79B9950

Blum CLIP top Hinge – 95° Blind Corner Overlay BLUMOTION Sprung – Nickel is engineered for cabinet doors installed in blind corner cabinet configurations where specialised hinge geometry is required to achieve correct door movement and alignment. Part of the **Blum CLIP top BLUMOTION hinge system**, this hinge integrates soft-close technology directly within the hinge mechanism, delivering smooth and controlled closing without the need for additional damping components. Manufactured to Blum's precision engineering standards, it ensures reliable performance in complex cabinet layouts.

The hinge features a **95° opening angle**, providing practical cabinet access while maintaining controlled door movement within restricted blind corner installations. Designed for **overlay cabinet door applications**, the final overlay position is determined by the selected mounting plate, allowing flexibility across different cabinet constructions. The hinge clips securely onto compatible Blum mounting plates using the **tool-free CLIP top system**, enabling efficient installation and straightforward removal during adjustment or maintenance.

Manufactured from durable steel with a **nickel-plated finish**, the hinge provides corrosion resistance and a neutral appearance suitable for most cabinet interiors. The hinge cup is **compatible with different boss fixing types depending on the selected variant**, allowing flexibility during installation depending on cabinet material and manufacturing requirements.

Product Features

- **95° opening angle** suitable for blind corner cabinet installations
- Integrated **BLUMOTION soft-close mechanism**
- Designed for **blind corner overlay cabinet door applications**
- Compatible with **multiple boss fixing types depending on variant**

- Durable **nickel-plated finish**
- **Tool-free CLIP hinge attachment**
- **Three-dimensional adjustment capability**

Product Benefits

- Provides smooth and quiet **soft-closing door operation**
- Enables hinge installation in **blind corner cabinet layouts**
- Supports flexible **overlay cabinet design**
- Allows installation flexibility through **different boss fixing options**
- Ensures accurate door alignment and consistent reveals
- Suitable for residential and light commercial cabinetry

Technical Characteristics

- Requires compatible **Blum CLIP top mounting plates**
- Designed to support **different boss fixing types depending on variant**
- Adjustable vertically, laterally and in depth
- Steel hinge construction with **nickel-plated protective finish**
- Suitable for **blind corner overlay cabinet constructions**
- Correct hinge and mounting plate pairing ensures optimal performance

Applications

Suitable for **blind corner overlay cabinet doors** used in kitchens, storage units and bespoke furniture where specialised hinge geometry is required to allow correct door movement within restricted cabinet spaces. The integrated **BLUMOTION soft-close mechanism** ensures controlled and quiet closing, while compatibility with **different boss fixing types depending on variant** allows installation across a variety of cabinet materials and manufacturing methods. The **nickel-plated finish** provides durability and a clean appearance suited to most cabinetry interiors.

Property	Value
Finish	Nickel

Property	Value
Opening angle (°)	95
Application	Overlay
Boss	Screw-on
Closing Mechanism	Sprung
Boss Drilling Depth (mm)	13
Max Door Thickness (mm)	28
Hinge Type	Blind Corner