



## Blum Clip Top Hinge – 95° Aluminum Door Overlay Sprung – Nickel – Screw-on

Variant code: 71T950A

**Blum CLIP top – 95° Overlay Sprung Hinge – Nickel** is designed to deliver reliable and consistent self-closing performance in overlay cabinet applications where a reduced opening angle is required. Incorporating an integrated **sprung mechanism**, the hinge provides controlled door movement without the need for additional closing components. The 95° opening angle makes it particularly suitable for installations where cabinet configuration or door thickness restricts the use of wider opening hinges.

Designed for **overlay cabinet doors**, the final overlay dimension is determined by mounting plate selection, allowing flexibility across a range of cabinet constructions. As part of the Blum CLIP top system, the hinge clips securely onto compatible mounting plates using a tool-free attachment method, enabling efficient installation and straightforward adjustment. Three-dimensional adjustment allows precise vertical, lateral and depth positioning to achieve accurate alignment and consistent door gaps.

The **Screw-On boss fixing** provides secure mechanical retention within the door and requires accurate hinge cup drilling preparation. Manufactured from durable nickel-plated steel, the hinge offers a clean and neutral finish suitable for a wide range of cabinetry styles while maintaining full compatibility within the Blum hinge platform.

---

### Product Features

- **95° opening angle** for controlled cabinet access
- Integrated **sprung mechanism** for self-closing action
- Designed for **overlay door applications**
- **Screw-On boss fixing**
- Durable **nickel-plated steel finish**

- Compatible with Blum **CLIP top mounting plates**
- Tool-free clip-on hinge assembly
- Three-dimensional adjustment capability

---

## Product Benefits

- Provides reliable and consistent self-closing performance
- Supports clean overlay cabinet aesthetics
- Ensures secure hinge retention with mechanical fixing
- Enables precise alignment and even door gaps
- Suitable for installations with reduced opening clearance
- Appropriate for residential and light commercial interiors

---

## Technical Characteristics

- Requires compatible Blum CLIP top mounting plates
- Screw-On boss requires correct hinge cup drilling preparation
- Adjustable vertically, laterally and in depth
- Designed for integration within Blum cabinet systems
- Suitable for standard overlay cabinet constructions
- Correct hinge and mounting plate pairing ensures optimal performance

---

## Applications

This hinge is intended for overlay cabinet door installations where a reduced opening angle is required due to cabinet layout or spatial constraints. The integrated **sprung mechanism**

ensures dependable closing performance, while the Screw-On fixing method provides secure and stable installation. It is commonly specified in kitchens, bedrooms and fitted furniture in residential and light commercial interiors requiring durability, precise alignment and reliable hinge operation.

Property	Value
Finish	Nickel
Opening angle (°)	95
Application	Overlay
Boss	Screw-on
Closing Mechanism	Sprung
Max Door Thickness (mm)	24
Type	Aluminum Frame