



Blum Clip Top Hinge III – 15° Overlay BLUMOTION Sprung – Nickel – Screw-on

Variant code: 79B9454

Blum CLIP top Hinge III – 15° Overlay BLUMOTION Sprung – Nickel is designed for cabinet doors installed on angled cabinet constructions where specialised hinge geometry is required to achieve correct door positioning. Part of the **Blum CLIP top BLUMOTION hinge system**, this hinge incorporates integrated soft-close technology within the hinge mechanism, ensuring smooth and controlled door closing without the need for additional damping components. Manufactured to Blum's precision engineering standards, it provides reliable performance in cabinetry requiring angled hinge configurations.

The hinge features a **15° hinge geometry**, making it suitable for cabinets installed on shallow angled or diagonal layouts commonly found in corner cabinetry and bespoke furniture designs. Designed for **overlay cabinet door applications**, the final overlay position is determined by the selected mounting plate, allowing flexibility across a range of cabinet constructions. The hinge clips securely onto compatible Blum mounting plates using the **tool-free CLIP top system**, enabling efficient installation and easy removal for adjustment or maintenance.

Manufactured from durable steel with a **nickel-plated finish**, the hinge provides corrosion resistance and a neutral appearance suitable for most cabinet interiors. The hinge cup uses a **screw-on boss fixing**, ensuring secure mechanical attachment to the cabinet door when installed into correctly prepared hinge cup drilling.

Product Features

- **15° hinge geometry** for angled cabinet installations
- Integrated **BLUMOTION soft-close mechanism**
- Designed for **overlay cabinet door applications**
- **Screw-on boss fixing**

- Durable **nickel-plated finish**
- **Tool-free CLIP hinge attachment**
- **Three-dimensional adjustment capability**

Product Benefits

- Provides smooth and quiet **soft-closing door operation**
- Enables hinge installation on **shallow angled cabinet constructions**
- Ensures secure installation with **screw-on fixing**
- Supports precise door alignment and consistent reveals
- Protects cabinet doors from closing impact
- Suitable for residential and light commercial cabinetry

Technical Characteristics

- Requires compatible **Blum CLIP top mounting plates**
- **Screw-on boss fixing** requires correct hinge cup drilling preparation
- Adjustable vertically, laterally and in depth
- Steel hinge construction with **nickel-plated protective finish**
- Suitable for **angled cabinet door constructions**
- Correct hinge and mounting plate pairing ensures optimal performance

Applications

Suitable for **overlay cabinet doors** used in angled cabinet constructions such as corner units, diagonal cabinets and bespoke furniture installations. The **15° hinge geometry** allows

correct door positioning on shallow angled cabinet layouts, while the integrated **BLUMOTION soft-close mechanism** ensures controlled and quiet closing. The **screw-on boss fixing** provides secure installation within standard cabinet door materials, making the hinge suitable for kitchens, wardrobes and fitted furniture requiring specialised hinge geometry and reliable soft-closing performance.

Property	Value
Finish	Nickel
Opening angle (°)	15
Application	Overlay
Boss	Screw-on
Closing Mechanism	Sprung
Boss Drilling Depth (mm)	13
Hinge Type	Angled