



## Blum Clip Top Hinge – 100° Overlay Sprung – Nickel – Screw-on

Variant code: 71M2550

Blum CLIP top Hinge – 100° Overlay Sprung – Nickel is designed for overlay cabinet door installations where reliable self-closing hinge performance is required. As part of the **Blum CLIP top hinge system**, this hinge combines precision engineering with efficient installation and accurate adjustment. The integrated **sprung hinge mechanism** ensures consistent self-closing action, delivering smooth and dependable door movement in everyday cabinet use.

The hinge provides a **100° opening angle**, offering practical access to cabinet interiors while maintaining stable hinge operation. Designed for **overlay cabinet door applications**, the final overlay position is determined by the selected mounting plate, allowing flexibility across a wide range of cabinet constructions and installation requirements.

The hinge clips securely onto compatible Blum mounting plates using the **tool-free CLIP top system**, enabling quick installation and easy removal for cabinet adjustment or maintenance. Integrated **three-dimensional adjustment** allows installers to accurately position the door vertically, laterally and in depth to achieve precise alignment and consistent door gaps.

This hinge supports **two boss fixing variations**, providing flexibility depending on cabinet manufacturing methods or installation preferences. **Screw-on boss fixing** provides secure mechanical attachment through screws, while **Knock-in boss fixing** uses dowel pins pressed into pre-drilled hinge cup holes for efficient installation. Manufactured from durable steel with a **nickel-plated finish**, the hinge provides corrosion resistance and a clean appearance suitable for most cabinet interiors.

---

### Product Features

- **100° opening angle** for practical cabinet access
- **Sprung hinge mechanism** for self-

closing action

- Designed for **overlay cabinet door applications**
- Compatible with **Screw-on and Knock-in boss fixing**
- Durable **nickel-plated steel finish**
- Part of the **Blum CLIP top hinge system**
- **Tool-free CLIP hinge attachment**
- **Three-dimensional adjustment capability**

---

## Product Benefits

- Provides **smooth and reliable self-closing performance**
- Supports standard **overlay cabinet configurations**
- Allows installation flexibility using **Screw-on or Knock-in fixing methods**
- Enables precise door alignment and consistent reveals
- Ensures durable hinge performance during everyday use
- Integrates seamlessly within the **Blum hinge platform**

---

## Technical Characteristics

- Requires compatible **Blum CLIP top mounting plates**
- Designed for **overlay cabinet door construction**
- **Screw-on boss fixing** requires hinge cup drilling and screw attachment
- **Knock-in boss fixing** uses dowel pins inserted into pre-drilled holes
- Adjustable vertically, laterally and in depth

- Steel hinge construction with **nickel protective finish**

---

## Applications

This hinge is intended for **overlay cabinet door installations** in kitchens, wardrobes, storage furniture and fitted cabinetry where dependable self-closing hinge performance is required. The **sprung hinge mechanism** ensures consistent closing action during everyday use. Compatibility with **Screw-on and Knock-in boss fixing options** allows flexible installation across different cabinet manufacturing methods, making the hinge suitable for both bespoke joinery projects and large-scale furniture production environments.

Property	Value
Finish	Nickel
Opening angle (°)	100
Application	Overlay
Boss	Screw-on
Closing Mechanism	Sprung
Boss Drilling Depth (mm)	10.5
Max Door Thickness (mm)	24
Hinge Type	Standard