SWS HARDWARE
Tel: 01626 333900
Email: info@swshardware.com



Cam Action Door Closer inc Semi-Radius Cover + Slidearm - Satin Nickel

Variant code: FL6241.SNP

Cam Action Door Closer with Semi-Radius Cover and Slide Arm is a **high-performance overhead door closer** engineered to provide exceptionally smooth door operation with minimal opening resistance. Designed for accessibility, fire safety and modern architectural applications, this **EN Size 2-4 power-adjustable** closer features an advanced cam action mechanism that assists compliance with **Approved Document M** and **BS 8300**, making it an ideal solution for commercial, healthcare, education and public buildings.

Renowned for its high efficiency and ease of opening, the closer features a **slimline 39mm projection** from the door, creating a discreet appearance while maintaining outstanding performance. The temperature-stable hydraulic fluid ensures reliable operation in ambient temperatures from **-15°C to +40°C**, providing consistent closing action in a wide range of environments.

Suitable for **doors up to 80kg and 1100mm wide**, the closer offers **variable EN Power Size 2-4 adjustment** and can be installed in **pull-side, push-side or transom mounting positions**, making it suitable for a wide variety of timber and metal doors. Successfully tested to **BS EN1154**, **CE Marked**, **Fire Tested to EN1634-1**, and **Certifire Approved**, it provides dependable performance for both fire-rated and non-fire-rated applications.

Backed by a **35-year manufacturer's guarantee**, this cam action closer delivers long-term reliability while offering a selection of architectural finishes to complement contemporary door hardware.

Product Features

- **Cam action overhead door closer**
- **Semi-radius cover included**
- **Slide arm included**
- **Available finishes:**
  - Silver
  - Satin Nickel
  - Antique Brass

Tel: 01626 333900
Email: info@swshardware.com

    - Satin Nickel (12106)
    - PVD Brass (11349)
- Variable **EN Power Size 2-4**
- Suitable for doors up to **80kg**
- Suitable for doors up to **1100mm wide**
- Advanced cam action mechanism for reduced opening force
- Assists compliance with **Approved Document M** and **BS 8300**
- Universal installation:
    - Pull-side mounting
    - Push-side mounting
    - Transom mounting
- Ultra-slim **39mm projection**
- Temperature-stable hydraulic fluid
- Operating temperature **-15°C to +40°C**
- Fire tested to **EN1634-1**
- **Certifire Approved**
- Successfully tested to **BS EN1154**
- **CE Marked**
- **35-year manufacturer's guarantee**

Product Benefits

- **Provides exceptionally smooth, low opening-force operation**
- **Supports accessibility requirements for Doc M compliant doors**
- **Slimline design enhances modern architectural aesthetics**
- Flexible installation for multiple mounting configurations
- Reliable operation across a wide operating temperature range
- Suitable for fire-rated door assemblies
- Durable commercial-grade construction for long service life
- Choice of finishes to coordinate with surrounding ironmongery

Technical Characteristics

- **Product Type:** Cam Action Door Closer
- **Mechanism:** Cam Action
- **Cover Type:** Semi-Radius Cover
- **Arm Type:** Slide Arm
- **Power Size:** Adjustable EN 2-4
- **Maximum Door Width:** 1100mm
- **Maximum Door Weight:** 80kg
- **Mounting Options:** Pull Side, Push Side or Transom
- **Projection:** 39mm
- **Operating Temperature:** -15°C to +40°C
- **Door Material:** Timber and Metal
- **Fire Rating:** EN1634-1

Tel: 01626 333900
Email: info@swshardware.com

- **Certification:** BS EN1154, CE Marked, Certifire Approved
- **Accessibility:** Assists BS 8300 / Approved Document M compliance
- **Available Finishes:**
  - Silver
  - Satin Nickel
  - Antique Brass
  - Satin Nickel (12106)
  - PVD Brass (11349)
- **Guarantee:** 35 Years

Applications

Cam Action Door Closer with Semi-Radius Cover and Slide Arm is ideal for **hospitals, healthcare facilities, care homes, schools, universities, offices, hotels, apartment buildings and other commercial or public buildings** where **accessibility, fire safety and architectural appearance** are important. Suitable for **timber and metal doors** up to **80kg**, it provides smooth, controlled closing with reduced opening force, helping meet **Doc M** and **BS 8300** requirements while offering a choice of finishes to complement modern architectural ironmongery.

Property	Value
Finish	Satin Nickel
Opening angle (°)	110
Warranty (Years)	35
Fire Tested (mins)	60
Max Door Width (mm)	1100
Max Door Weight (kg)	80
Power Size	EN 2–4 Adjustable
Certification	BS EN 1154, CE Marked, BS 8300, EN 1634-1