



Blum Clip Top Hinge – 107° Overlay Sprung – Nickel – Screw-on

Variant code: 75T1550

Blum CLIP top Hinge – 107° Overlay Sprung – Nickel is designed to provide reliable self-closing performance for overlay cabinet door applications. Manufactured by **Blum**, a globally recognised specialist in cabinet hardware, this hinge forms part of the established **CLIP top hinge system**, combining precision engineering with efficient installation and adjustment. The integrated sprung mechanism delivers controlled closing action, ensuring cabinet doors return smoothly and consistently to the closed position during everyday use.

The hinge features a **107° opening angle**, providing practical access to cabinet interiors while maintaining stable hinge movement and dependable door operation. Designed specifically for **overlay cabinet door configurations**, the final overlay position is determined by the selected mounting plate, allowing flexibility across different cabinet constructions and joinery systems. The hinge clips securely onto compatible Blum mounting plates using the **tool-free CLIP top system**, enabling quick installation and straightforward removal when adjustment or maintenance is required.

Manufactured from durable steel with a **nickel-plated finish**, the hinge provides corrosion resistance and a clean, neutral appearance suitable for most cabinet interiors. The hinge cup is **compatible with different boss fixing types depending on the selected variant**, allowing flexibility during installation based on cabinet material, drilling preparation and manufacturing requirements.

Product Features

- **107° opening angle** for practical cabinet access
- Integrated **sprung self-closing mechanism**
- Designed for **overlay cabinet door applications**
- Compatible with **multiple boss fixing types depending on variant**

- Durable **nickel-plated steel construction**
- **Tool-free CLIP top hinge attachment**
- **Three-dimensional adjustment capability**

Product Benefits

- Provides reliable **self-closing hinge performance**
- Supports clean and consistent **overlay cabinet design**
- Allows installation flexibility through **different boss fixing options**
- Enables precise door alignment and consistent reveals
- Offers dependable performance under regular daily use
- Suitable for residential and light commercial cabinetry

Technical Characteristics

- Requires compatible **Blum CLIP top mounting plates**
- Supports **different boss fixing types depending on variant**
- Adjustable vertically, laterally and in depth
- Steel hinge construction with **nickel-plated protective finish**
- Designed for integration within **Blum cabinet hardware systems**
- Correct hinge and mounting plate pairing ensures optimal performance

Applications

This hinge is suitable for **overlay cabinet doors** used in kitchens, wardrobes, storage units and fitted furniture where dependable self-closing performance and accurate door alignment are required. The **107° opening angle** provides practical access to cabinet interiors while maintaining smooth hinge movement. Compatibility with **different boss fixing types depending on variant** allows installation across a wide range of cabinet materials and production methods while maintaining consistent hinge performance.

| Property | Value |
|----------|--------|
| Finish | Nickel |

| Property | Value |
|--------------------------|--------------|
| Opening angle (°) | 107 |
| Application | Overlay |
| Boss | Screw-on |
| Closing Mechanism | Sprung |
| Boss Drilling Depth (mm) | 11.5 |
| Max Door Thickness (mm) | 24 |
| Hinge Type | Standard |