



Blum Clip Top Hinge – 107° Overlay BLUMOTION Sprung – Onyx Black – Screw-on

Variant code: 75B1550-OB

Blum CLIP top Hinge – 107° Overlay BLUMOTION Sprung – Nickel is designed to deliver smooth, controlled door movement for overlay cabinet door applications. Part of the **Blum CLIP top BLUMOTION hinge system**, this hinge integrates soft-close technology directly into the hinge mechanism, ensuring doors close quietly and consistently without the need for additional damping components. Manufactured to Blum's precision engineering standards, it provides dependable performance across a wide range of cabinetry installations.

The hinge features a **107° opening angle**, offering practical access to cabinet interiors while maintaining stable hinge movement and controlled closing action. Designed for **overlay cabinet door configurations**, the final overlay position is determined by the selected mounting plate, allowing flexibility across different cabinet constructions. The hinge clips securely onto compatible Blum mounting plates using the **tool-free CLIP top system**, enabling fast installation and simple removal during adjustment or maintenance.

Manufactured from durable steel with a **nickel-plated finish**, the hinge offers corrosion resistance and a neutral appearance suitable for most cabinet interiors. The hinge cup is designed to accommodate **boss fixing variations**, allowing flexibility in installation depending on cabinet material and manufacturing processes.

Product Features

- **107° opening angle**
- Integrated **BLUMOTION soft-close mechanism**
- Designed for **overlay cabinet door applications**
- Compatible with **boss fixing variations**
- Durable **nickel-plated finish**

- **Tool-free CLIP hinge attachment**
- **Three-dimensional adjustment capability**

Product Benefits

- Provides smooth and quiet **soft-closing performance**
- Protects cabinet doors from closing impact
- Allows flexible installation through **boss fixing options**
- Enables precise door alignment and consistent reveals
- Ensures reliable long-term hinge performance
- Suitable for residential and light commercial cabinetry

Technical Characteristics

- Requires compatible **Blum CLIP top mounting plates**
- Designed to accommodate **screw-on boss fixing configuration**
- Adjustable vertically, laterally and in depth
- Steel hinge construction with **nickel-plated protective finish**
- Suitable for **overlay cabinet constructions**
- Correct hinge and mounting plate pairing ensures optimal performance

Applications

Suitable for **overlay cabinet doors** used in kitchens, wardrobes, storage units and fitted furniture where controlled and quiet door closing is required. The integrated **BLUMOTION soft-close mechanism** ensures smooth operation, while compatibility with **boss fixing variations**

allows installation across different cabinet materials and manufacturing methods. The **nickel finish** provides durability and a clean appearance suitable for most cabinetry interiors.

Property	Value
Finish	Onyx Black
Opening angle (°)	107
Application	Overlay
Boss	Screw-on
Closing Mechanism	Sprung
Boss Drilling Depth (mm)	11.5
Max Door Thickness (mm)	24
Hinge Type	Standard