



Blum Clip Top Hinge – 110° CRISTALLO Overlay BLUMOTION Sprung – Nickel – Glue-on

Variant code: 71B4500C

Blum CLIP top BLUMOTION 110° full overlay hinge with glue-on fixing is designed for cabinet doors requiring integrated soft-close performance where conventional cup drilling is not suitable. Incorporating **BLUMOTION soft-close technology** within the hinge mechanism, it delivers smooth and controlled closing without the need for additional damping components.

With a **110° opening angle**, the hinge provides practical access to cabinet interiors while maintaining stable and consistent door movement. Designed for **full overlay applications**, it allows the door to fully cover the cabinet side panel, supporting clean exterior lines and uniform spacing across cabinet runs. The hinge clips securely onto compatible CLIP top mounting plates using Blum's tool-free attachment system, enabling straightforward installation and removal during fitting or adjustment.

The **glue-on fixing method** is intended for applications such as glass or thin-profile doors where traditional hinge cup drilling is not possible. The hinge plate bonds directly to the door surface using a suitable adhesive system, providing secure attachment without compromising material integrity. Manufactured from steel with a durable **nickel-plated finish**, the hinge offers a neutral appearance suitable for a wide range of cabinetry styles. Three-dimensional adjustment allows precise vertical, lateral and depth positioning to achieve accurate alignment.

Product Features

- **110° opening angle** for standard cabinet access
- Integrated **BLUMOTION soft-close mechanism**
- Designed for **full overlay door applications**
- **Glue-on fixing** for non-drill installations

- Durable **nickel-plated steel finish**
- Compatible with Blum **CLIP top mounting plates**
- Three-dimensional adjustment capability

Product Benefits

- Provides smooth and controlled door closing
- Suitable for glass or thin-profile doors
- Eliminates the need for hinge cup drilling
- Maintains clean full overlay cabinet aesthetics
- Enables precise alignment and consistent door gaps
- Suitable for residential and light commercial interiors

Technical Characteristics

- Requires compatible Blum CLIP top mounting plates
- Glue-on installation requires correct adhesive selection and surface preparation
- Adjustable vertically, laterally and in depth
- Designed for integration within Blum cabinet systems
- Suitable for full overlay cabinet constructions
- Correct installation and curing procedures are essential for optimal performance

Applications

This hinge is intended for full overlay cabinet door installations where traditional cup drilling is not possible, including glass-fronted cabinets and specialist material doors. The integrated

BLUMOTION soft-close mechanism ensures controlled and quiet closing, while the glue-on fixing method allows secure attachment without penetrating the door surface. It is commonly specified in kitchens, display cabinets and bespoke fitted furniture requiring soft-close performance combined with non-drill hinge installation.

| Property | Value |
|-------------------|------------|
| Finish | Nickel |
| Opening angle (°) | 110 |
| Application | Overlay |
| Boss | Glue-on |
| Closing Mechanism | Soft Close |
| Hinge Type | Glass Door |