SWS HARDWARE
Tel: 01626 333900
Email: info@swshardware.com



Blum Clip Top Hinge - 110° Special Overlay BLUMOTION Sprung - Nickel - Screw-on

Variant code: 73B3550-NI

Blum Clip Top Hinge - 110° Overlay Sprung - Nickel is designed to provide reliable self-closing performance for overlay cabinet door applications. Part of the **Blum CLIP top hinge system**, this hinge incorporates an integrated sprung mechanism that delivers controlled closing action and consistent door movement. Engineered to Blum's precision standards, it ensures dependable operation and long-term durability across a wide range of cabinetry installations.

The hinge features a **110° opening angle**, offering practical access to cabinet interiors while maintaining stable hinge performance. Designed for **overlay cabinet door configurations**, the final overlay position is determined by the selected mounting plate, allowing flexibility across different cabinet constructions. The hinge clips securely onto compatible Blum mounting plates using the **tool-free CLIP top system**, enabling quick installation and straightforward removal for adjustment or maintenance.

Manufactured from durable steel with a **nickel-plated finish**, the hinge provides corrosion resistance and a clean, neutral appearance suitable for most cabinet interiors. The hinge cup is designed to accommodate **boss fixing variations**, allowing flexibility in installation depending on cabinet material and manufacturing methods.

Product Features

- **110° opening angle**
- Integrated **sprung self-closing mechanism**
- Designed for **overlay cabinet door applications**
- Compatible with **boss fixing variations**
- Durable **nickel-plated finish**
- **Tool-free CLIP hinge attachment**

SWS HARDWARE
Tel: 01626 333900
Email: info@swshardware.com

- **Three-dimensional adjustment capability**

Product Benefits

- Provides reliable **self-closing hinge performance**
- Supports clean and consistent **overlay cabinet design**
- Allows flexible installation through **boss fixing options**
- Enables precise door alignment and consistent reveals
- Ensures dependable long-term hinge operation
- Suitable for residential and light commercial cabinetry

Technical Characteristics

- Requires compatible **Blum CLIP top mounting plates**
- Designed to accommodate **different boss fixing configurations depending on variant**
- Adjustable vertically, laterally and in depth
- Steel hinge construction with **nickel-plated protective finish**
- Suitable for **overlay cabinet constructions**
- Correct hinge and mounting plate pairing ensures optimal performance

Applications

Suitable for **overlay cabinet doors** used in kitchens, wardrobes, storage units and fitted furniture where reliable hinge performance and consistent door alignment are required. The **sprung hinge mechanism** provides controlled self-closing action, while compatibility with **boss fixing variations** allows flexible installation across

SWS HARDWARE

Tel: 01626 333900
Email: info@swshardware.com

different cabinet materials and manufacturing methods. The **nickel-plated finish** offers durability and a neutral appearance suited to most cabinet interiors.

Property	Value
Finish	Nickel
Opening angle (°)	110
Application	Overlay
Boss	Screw-on
Closing Mechanism	Sprung
Boss Drilling Depth (mm)	13
Max Door Thickness (mm)	26
Hinge Type	Special