



Blum Clip Top Hinge – 155° Nil Protrusion Half Overlay BLUMOTION Sprung – Nickel – Inserta

Variant code: 71B7690-NI

The **CLIP top BLUMOTION 155° wide-angle hinge** is designed for applications where increased door opening access is required without compromising controlled closing performance. Engineered by Blum for precision cabinet construction, this hinge combines a **wide 155° opening angle** with integrated **BLUMOTION soft-close technology**, allowing doors to open fully while closing smoothly and quietly.

The O-protrusion design enables internal drawers or pull-outs to operate without obstruction when the door is open, making it particularly suitable for cabinetry that incorporates internal storage solutions. The hinge integrates seamlessly into the CLIP top system, allowing tool-free attachment and removal from the mounting plate for efficient installation and adjustment.

Product Features

- **155° wide opening angle** for enhanced cabinet access
- Integrated **BLUMOTION soft-close mechanism**
- O-protrusion design to prevent interference with internal drawers
- Compatible with the **CLIP top mounting plate system**
- Screw-on boss fixing for secure installation
- Three-dimensional adjustment capability
- Nickel-plated steel construction

Product Benefits

- Provides improved accessibility for wide cabinets and pull-out systems

- Ensures controlled, quiet door closing
- Allows internal drawer systems to function without door obstruction
- Simplifies installation and on-site adjustment
- Supports consistent alignment across cabinetry
- Contributes to long-term durability in high-use environments

Technical Characteristics

- Designed for use with compatible Blum CLIP top mounting plates
- Suitable for overlay applications requiring wide-angle access
- Three-way adjustment supports accurate door alignment
- Screw-on boss requires appropriate drilling preparation
- Intended for use in conjunction with Blum hinge system components
- Regular inspection and correct installation ensure optimal performance

Applications

This hinge is suited to kitchen, bedroom and fitted furniture applications where enhanced door opening is required, particularly cabinets incorporating internal pull-outs or drawer systems. The 155° opening angle allows improved access to cabinet interiors while maintaining controlled soft-close action. It is commonly specified in premium residential kitchens and bespoke cabinetry where both functionality and long-term performance are priorities.

| Property | Value |
|-------------------|--------|
| Finish | Nickel |
| Opening angle (°) | 155 |

| Property | Value |
|--------------------------|--------------|
| Application | Half Overlay |
| Boss | Inserta |
| Closing Mechanism | Soft Close |
| Boss Drilling Depth (mm) | 11.7 |
| Max Door Thickness (mm) | 31 |
| Type | Wide Angled |