



## Blum Clip Top Hinge II – 30° Overlay BLUMOTION Sprung – Nickel – Screw-on

Variant code: 79B9556

**Blum CLIP top Hinge II – 30° Overlay BLUMOTION Sprung – Nickel** is engineered for cabinet doors installed in angled cabinet constructions where specialised hinge geometry is required to achieve correct door positioning. Part of the **Blum CLIP top BLUMOTION hinge system**, this hinge integrates soft-close technology directly within the hinge mechanism, ensuring smooth and controlled door closing without additional damping components. Manufactured to Blum's precision engineering standards, it delivers dependable performance in cabinetry where angled hinge configurations are necessary.

The hinge features a **30° hinge geometry**, making it suitable for cabinets installed on angled or diagonal layouts often used in corner cabinetry and bespoke furniture designs. Designed for **overlay cabinet door applications**, the final overlay position is determined by the selected mounting plate, allowing flexibility across a wide range of cabinet constructions. The hinge clips securely onto compatible Blum mounting plates using the **tool-free CLIP top system**, enabling quick installation and straightforward removal for adjustment or maintenance.

Manufactured from durable steel with a **nickel-plated finish**, the hinge offers corrosion resistance and a neutral appearance suited to most cabinet interiors. The hinge cup is **compatible with different boss fixing types depending on the selected variant**, allowing flexibility during installation based on cabinet material and manufacturing requirements.

---

### Product Features

- **30° hinge geometry** for angled cabinet installations
- Integrated **BLUMOTION soft-close mechanism**
- Designed for **overlay cabinet door applications**
- Compatible with **multiple boss fixing types depending on variant**
- Durable **nickel-plated finish**

- **Tool-free CLIP hinge attachment**
- **Three-dimensional adjustment capability**

---

## Product Benefits

- Provides smooth and quiet **soft-closing door operation**
- Enables hinge installation on **angled cabinet constructions**
- Allows installation flexibility through **different boss fixing options**
- Supports precise door alignment and consistent reveals
- Protects cabinet doors from closing impact
- Suitable for residential and light commercial cabinetry

---

## Technical Characteristics

- Requires compatible **Blum CLIP top mounting plates**
- Designed to support **different boss fixing types depending on variant**
- Adjustable vertically, laterally and in depth
- Steel hinge construction with **nickel-plated protective finish**
- Suitable for **angled cabinet door constructions**
- Correct hinge and mounting plate pairing ensures optimal performance

---

## Applications

Suitable for **overlay cabinet doors** used in angled cabinet constructions such as corner units, diagonal cabinets and bespoke furniture installations. The **30° hinge geometry** allows correct door positioning in cabinets where angled layouts are required. The integrated **BLUMOTION soft-close mechanism** ensures controlled and quiet door closing, while compatibility with **different boss fixing types depending on variant** allows installation across a variety of cabinet materials and manufacturing methods.

Property	Value
Finish	Nickel
Opening angle (°)	30
Application	Overlay

Property	Value
Boss	Screw-on
Closing Mechanism	Sprung
Hinge Type	Angled