



Blum Clip Top Hinge – 95° Thick Door Overlay BLUMOTION Sprung – Onyx Black – Screw-on

Variant code: 71B9550-OB

Blum CLIP top BLUMOTION 95° Overlay Hinge – **Onyx Black** is designed for cabinet doors requiring controlled closing performance in overlay applications where a reduced opening angle is preferred. Incorporating integrated **BLUMOTION soft-close technology**, the hinge ensures smooth and quiet closing without the need for additional damping components, delivering refined movement and long-term reliability.

With a **95° opening angle**, this hinge is particularly suited to installations where door thickness, internal fittings or cabinet configuration limit the use of wider opening hinges. Designed for **overlay cabinet doors**, the final overlay dimension is determined by mounting plate selection, allowing flexibility within cabinet construction. The hinge clips securely onto compatible Blum CLIP top mounting plates using the tool-free attachment system, enabling efficient installation and straightforward removal during adjustment.

This hinge is available in both **Screw-on and Inserta boss fixing configurations**, providing flexibility across different installation preferences and production environments. The Screw-on version offers traditional mechanical retention within the hinge cup and requires appropriate drilling preparation. The Inserta version incorporates integrated expansion dowels for rapid installation into pre-drilled hinge cup holes, reducing fitting time while ensuring secure anchoring. Finished in durable **Onyx Black**, the hinge supports coordinated hardware specification in contemporary dark cabinetry schemes while remaining fully compatible within the Blum hinge platform. Three-dimensional adjustment enables precise vertical, lateral and depth positioning to achieve accurate alignment and consistent door gaps.

Product Features

- **95° opening angle** for controlled cabinet access

- Integrated **BLUMOTION soft-close mechanism**
- Designed for **overlay door applications**
- Available in **Screw-on and Inserta boss fixing options**
- Durable **Onyx Black finish**
- Compatible with Blum **CLIP top mounting plates**
- Tool-free clip-on hinge assembly
- Three-dimensional adjustment capability

Product Benefits

- Provides smooth and quiet door closing
- Suitable for installations with limited opening clearance
- Offers installation flexibility for different production methods
- Ensures secure hinge retention
- Coordinates visually with contemporary dark cabinetry
- Enables precise alignment and consistent reveals
- Suitable for residential and light commercial interiors

Technical Characteristics

- Requires compatible Blum CLIP top mounting plates
- Screw-on version requires correct hinge cup drilling preparation
- Inserta version uses integrated expansion dowels for rapid installation
- Adjustable vertically, laterally and in depth
- Designed for integration within Blum cabinet systems

- Suitable for thicker or space-restricted door applications
- Correct hinge and mounting plate pairing ensures optimal performance

Applications

This hinge is intended for overlay cabinet door installations where a reduced opening angle is required, such as cabinets with thicker doors or spatial constraints. The integrated **BLUMOTION soft-close mechanism** ensures controlled and quiet closing performance, while the availability of **Screw-on and Inserta fixing options** provides flexibility for both bespoke joinery and volume cabinet production. The **Onyx Black finish** makes it particularly suitable for contemporary kitchens, fitted furniture and dark cabinetry schemes in residential and light commercial interiors.

Property	Value
Finish	Onyx Black
Opening angle (°)	95
Application	Overlay
Boss	Screw-on
Closing Mechanism	Soft Close
Boss Drilling Depth (mm)	12.3
Max Door Thickness (mm)	32
Hinge Type	Profile Door