



## Blum Clip Top Hinge – 95° Thick Door Overlay BLUMOTION Sprung – Nickel – Inserta

Variant code: 71B9590-NI

The **Blum CLIP top BLUMOTION 95° overlay hinge** is designed for cabinet doors requiring controlled closing performance in overlay applications where a reduced opening angle is preferred. Incorporating integrated **BLUMOTION soft-close technology**, the hinge ensures smooth and quiet closing without the need for additional damping components.

With a **95° opening angle**, the hinge is particularly suited to installations where door thickness or cabinet configuration limits the use of wider opening hinges. Designed for **overlay cabinet doors**, the final overlay dimension is determined by mounting plate selection, providing flexibility within cabinet construction. The hinge clips securely onto compatible CLIP top mounting plates using Blum's tool-free attachment system, allowing efficient installation and straightforward removal during adjustment.

The **Screw-On boss fixing** provides secure mechanical retention within the door and requires appropriate drilling preparation. Manufactured from steel with a durable **nickel-plated finish**, the hinge offers a neutral appearance suitable for a wide range of cabinetry styles. Three-dimensional adjustment enables precise vertical, lateral and depth positioning to achieve accurate alignment and consistent door gaps.

---

### Product Features

- **95° opening angle** for controlled cabinet access
- Integrated **BLUMOTION soft-close mechanism**
- Designed for **overlay door applications**
- **Screw-On boss fixing**
- Durable **nickel-plated steel finish**
- Compatible with Blum **CLIP top**

**mounting plates**

- Three-dimensional adjustment capability

---

**Product Benefits**

- Provides smooth and quiet door closing
- Suitable for installations with limited opening clearance
- Ensures secure hinge retention with mechanical fixing
- Supports clean overlay cabinet aesthetics
- Enables precise alignment and consistent reveals
- Suitable for residential and light commercial interiors

---

**Technical Characteristics**

- Requires compatible Blum CLIP top mounting plates
- Screw-On boss requires correct drilling preparation
- Adjustable vertically, laterally and in depth
- Designed for integration within Blum cabinet systems
- Suitable for thicker or space-restricted door applications
- Correct hinge and mounting plate pairing ensures optimal performance

Property	Value
Finish	Nickel
Opening angle (°)	95
Application	Overlay

Property	Value
Boss	Inserta
Closing Mechanism	Soft Close
Boss Drilling Depth (mm)	12.3
Max Door Thickness (mm)	32
Type	Profile Door