



Blum Clip Top Hinge – 95° Thick Door Overlay BLUMOTION Sprung – Nickel – Inserta

Variant code: 71B9590-NI

Blum CLIP top BLUMOTION 95° Overlay Hinge – Nickel is designed for cabinet doors requiring controlled closing performance in overlay applications where a reduced opening angle is preferred. Incorporating integrated **BLUMOTION soft-close technology**, the hinge ensures smooth and quiet closing without the need for additional damping components, delivering refined movement and long-term reliability.

With a **95° opening angle**, the hinge is particularly suited to installations where door thickness, internal fittings or cabinet configuration limit the use of wider opening hinges. Designed for **overlay cabinet doors**, the final overlay dimension is determined by mounting plate selection, providing flexibility within cabinet construction. The hinge clips securely onto compatible Blum CLIP top mounting plates using the tool-free attachment system, allowing efficient installation and straightforward removal during adjustment.

This hinge is available in both **Screw-on and Inserta boss fixing configurations**, offering flexibility across different installation preferences and production environments. The Screw-on version provides traditional mechanical retention within the hinge cup and requires correct drilling preparation. The Inserta version incorporates integrated expansion dowels for rapid installation into pre-drilled hinge cup holes, reducing fitting time while ensuring secure anchoring. Manufactured from steel with a durable **nickel-plated finish**, the hinge offers a neutral appearance suitable for a wide range of cabinetry styles. Three-dimensional adjustment enables precise vertical, lateral and depth positioning to achieve accurate alignment and consistent door gaps.

Product Features

- **95° opening angle** for controlled cabinet access
- Integrated **BLUMOTION soft-close**

mechanism

- Designed for **overlay door applications**
- Available in **Screw-on and Inserta boss fixing options**
- Durable **nickel-plated steel finish**
- Compatible with Blum **CLIP top mounting plates**
- Tool-free clip-on hinge assembly
- Three-dimensional adjustment capability

Product Benefits

- Provides smooth and quiet door closing
- Suitable for installations with limited opening clearance
- Offers installation flexibility for different production methods
- Ensures secure hinge retention
- Supports clean overlay cabinet aesthetics
- Enables precise alignment and consistent reveals
- Suitable for residential and light commercial interiors

Technical Characteristics

- Requires compatible Blum CLIP top mounting plates
- Screw-on version requires correct hinge cup drilling preparation
- Inserta version uses integrated expansion dowels for rapid installation
- Adjustable vertically, laterally and in depth
- Designed for integration within Blum cabinet systems

- Suitable for thicker or space-restricted door applications
- Correct hinge and mounting plate pairing ensures optimal performance

| Property | Value |
|--------------------------|--------------|
| Finish | Nickel |
| Opening angle (°) | 95 |
| Application | Overlay |
| Boss | Inserta |
| Closing Mechanism | Soft Close |
| Boss Drilling Depth (mm) | 12.3 |
| Max Door Thickness (mm) | 32 |
| Hinge Type | Profile Door |