



Blum Clip Top Hinge – 95° Inset Unsprung – Nickel – Screw-on

Variant code: 70T9750.TL-NI

Blum CLIP top Hinge – 95° Inset Unsprung – Nickel is designed for inset cabinet door installations where controlled hinge movement is required without an integrated closing spring. As part of the **Blum CLIP top hinge system**, this hinge delivers dependable performance and precise adjustment while allowing the door to move freely. The **unsprung hinge mechanism** makes it particularly suitable for cabinetry using push-to-open mechanisms or external closing devices where hinge spring tension is not required.

The hinge features a **95° opening angle**, providing controlled access to cabinet interiors while maintaining stable hinge operation. Designed specifically for **inset cabinet door applications**, the door sits flush within the cabinet opening to create clean furniture lines and consistent reveals. The final door position is determined by the selected mounting plate, allowing flexibility across a range of cabinet constructions.

The hinge clips securely onto compatible Blum mounting plates using the **tool-free CLIP top system**, enabling quick installation and straightforward removal during cabinet adjustment or maintenance. Integrated **three-dimensional adjustment** allows precise vertical, lateral and depth positioning to achieve accurate door alignment and even door gaps.

This variant uses **Screw-on boss fixing**, providing secure mechanical attachment within the cabinet door when installed into correctly prepared hinge cup drilling. The screw-on fixing method ensures strong retention within the door material and is commonly used in both bespoke joinery and cabinet manufacturing environments. Manufactured from durable steel with a **nickel-plated finish**, the hinge offers corrosion resistance and a clean, neutral appearance suitable for most cabinet interiors.

Product Features

- **95° opening angle** for controlled cabinet access

- **Unsprung hinge mechanism** allowing free door movement
- Designed for **inset cabinet door applications**
- **Screw-on boss fixing**
- Durable **nickel-plated steel finish**
- Part of the **Blum CLIP top hinge system**
- **Tool-free CLIP hinge attachment**
- **Three-dimensional adjustment capability**

Product Benefits

- Suitable for cabinets using **push-to-open or external closing systems**
- Supports clean **flush inset cabinet designs**
- Ensures secure hinge installation through **Screw-on boss fixing**
- Enables precise door alignment and consistent reveals
- Provides reliable hinge performance during daily use
- Integrates seamlessly within the **Blum hinge platform**

Technical Characteristics

- Requires compatible **Blum CLIP top mounting plates**
- Designed for **inset cabinet door construction**
- **Screw-on boss fixing requires correct hinge cup drilling preparation**
- Adjustable vertically, laterally and in depth
- Steel hinge construction with **nickel protective finish**

- Correct hinge and mounting plate pairing ensures optimal door performance

Applications

This hinge is intended for **inset cabinet door installations** in kitchens, wardrobes, display cabinets and fitted furniture where free hinge movement is required. The **unsprung hinge design** allows the hinge to be used with push-to-open mechanisms or external closing systems. The **Screw-on boss fixing** ensures secure hinge attachment within the cabinet door, making it suitable for both bespoke joinery projects and cabinet manufacturing environments requiring durability, precision and consistent door alignment.

Property	Value
Finish	Nickel
Opening angle (°)	95
Application	Inset
Boss	Screw-on
Closing Mechanism	Unsprung
Boss Drilling Depth (mm)	12.3
Max Door Thickness (mm)	32
Hinge Type	Profile Door