



## Blum Clip Top Hinge – 95° Thick Door Half Overlay Sprung – Nickel – Screw-on

Variant code: 71T9650

**Blum CLIP top – 95° Half Overlay Sprung Hinge – Nickel** is designed to deliver consistent and reliable door movement in cabinet installations where a reduced opening angle is required. Incorporating an integrated **sprung mechanism**, this hinge provides controlled closing action without additional components, making it suitable for everyday cabinetry applications.

With a **95° opening angle**, the hinge is particularly suited to installations where cabinet configuration or door thickness limits the use of wider opening hinges. Designed for **half overlay cabinet doors**, it allows adjacent doors to share a central cabinet panel while maintaining precise alignment and consistent gaps. As part of the Blum CLIP top system, the hinge clips securely onto compatible mounting plates, enabling tool-free attachment and efficient installation.

The **Screw-On boss fixing** provides secure mechanical retention within the door and requires accurate drilling preparation. Manufactured from steel with a durable **nickel-plated finish**, the hinge integrates seamlessly into a wide range of cabinetry styles. Three-dimensional adjustment enables precise vertical, lateral and depth positioning for accurate alignment.

---

### Product Features

- **95° opening angle** for controlled cabinet access
- Integrated **sprung mechanism**
- Designed for **half overlay door applications**
- **Screw-On boss fixing**
- Durable **nickel-plated steel finish**
- Compatible with Blum **CLIP top mounting plates**
- Tool-free clip-on hinge assembly

- Three-dimensional adjustment capability

---

## Product Benefits

- Provides reliable and consistent sprung closing action
- Supports efficient cabinet layouts using shared panels
- Ensures secure hinge retention with mechanical fixing
- Enables precise alignment and even door gaps
- Suitable for installations with reduced opening clearance
- Appropriate for residential and light commercial interiors

---

## Technical Characteristics

- Requires compatible Blum CLIP top mounting plates
- Screw-On boss requires correct drilling preparation
- Adjustable vertically, laterally and in depth
- Designed for integration within Blum cabinet systems
- Suitable for thicker or space-restricted applications
- Correct hinge and mounting plate pairing ensures optimal performance

---

## Applications

This hinge is intended for half overlay cabinet door installations where a reduced opening angle is required due to cabinet layout or spatial constraints. The integrated **sprung mechanism** ensures dependable closing performance, while the half overlay configuration supports efficient cabinet design in multi-door units. It is commonly specified in kitchens, bedrooms and fitted furniture in residential and light commercial

interiors requiring durability and precise alignment.

Property	Value
Finish	Nickel
Opening angle (°)	95
Application	Half Overlay
Boss	Screw-on
Closing Mechanism	Sprung
Boss Drilling Depth (mm)	12.3
Max Door Thickness (mm)	32
Type	Profile Door