



Blum Clip Top Hinge – 95° Overlay Unsprung – Onyx Black – Screw-on

Variant code: 70T9550.TL-OB

Blum CLIP top Hinge – 95° Overlay Unsprung – Onyx Black is designed for overlay cabinet door installations where controlled hinge movement is required without an integrated closing spring. As part of the **Blum CLIP top hinge system**, this hinge delivers reliable hinge performance and precise adjustment while allowing the door to move freely. The **unsprung hinge mechanism** makes it suitable for cabinetry using push-to-open mechanisms or external closing devices where hinge spring tension is not required.

The hinge features a **95° opening angle**, providing controlled access to cabinet interiors while maintaining stable hinge operation. Designed for **overlay cabinet door applications**, the final overlay position is determined by the selected mounting plate, allowing flexibility across different cabinet constructions and installation requirements.

The hinge clips securely onto compatible Blum mounting plates using the **tool-free CLIP top system**, enabling quick installation and straightforward removal during cabinet adjustment or maintenance. Integrated **three-dimensional adjustment** allows installers to accurately position the door vertically, laterally and in depth to achieve precise alignment and consistent door gaps.

This variant uses **Screw-on boss fixing**, providing secure mechanical attachment within the cabinet door when installed into correctly prepared hinge cup drilling. The screw-on fixing method offers strong retention within the door material and is widely used in both bespoke joinery and cabinet manufacturing environments. Manufactured from durable steel and finished in **Onyx Black**, the hinge supports coordinated dark interior hardware schemes while maintaining corrosion resistance and long-term durability.

Product Features

- **95° opening angle** for controlled cabinet access

- **Unsprung hinge mechanism** allowing free door movement
- Designed for **overlay cabinet door applications**
- **Screw-on boss fixing**
- Durable **Onyx Black finish**
- Part of the **Blum CLIP top hinge system**
- **Tool-free CLIP hinge attachment**
- **Three-dimensional adjustment capability**

Product Benefits

- Suitable for cabinets using **push-to-open or external closing systems**
- Ensures secure hinge installation through **Screw-on boss fixing**
- Supports coordinated **dark cabinet hardware finishes**
- Enables precise door alignment and consistent reveals
- Provides reliable hinge performance in everyday use
- Integrates seamlessly within the **Blum hinge platform**

Technical Characteristics

- Requires compatible **Blum CLIP top mounting plates**
- Designed for **overlay cabinet door construction**
- **Screw-on boss fixing requires correct hinge cup drilling preparation**
- Adjustable vertically, laterally and in depth
- Steel hinge construction with **Onyx Black protective finish**

- Correct hinge and mounting plate pairing ensures optimal door performance

Applications

This hinge is intended for **overlay cabinet door installations** in kitchens, wardrobes, storage furniture and fitted cabinetry where free hinge movement is required. The **unsprung hinge design** allows the hinge to work with push-to-open mechanisms or external closing systems. The **Screw-on boss fixing** provides secure hinge attachment within the cabinet door, making it suitable for both bespoke joinery projects and cabinet manufacturing environments requiring durability, precision and coordinated dark hardware finishes.

Property	Value
Finish	Onyx Black
Opening angle (°)	95
Application	Overlay
Boss	Screw-on
Closing Mechanism	Unsprung
Boss Drilling Depth (mm)	12.3
Hinge Type	Profile Door