



## Blum Clip Top Hinge – 95° Thick Door Half Overlay BLUMOTION Sprung – Onyx Black– Screw-on

Variant code: 71B9650-OB

The **Blum CLIP top BLUMOTION 95° half overlay hinge** is designed for cabinet doors requiring integrated soft-close performance in half overlay applications where a reduced opening angle is preferred. Incorporating **BLUMOTION soft-close technology** within the hinge mechanism, it ensures smooth and controlled closing without the need for additional damping components.

With a **95° opening angle**, the hinge is particularly suited to installations where cabinet configuration or door thickness limits the use of wider opening hinges. Designed for **half overlay cabinet doors**, it allows adjacent doors to share a central cabinet panel, supporting efficient cabinet layouts in multi-door configurations. The hinge clips securely onto compatible CLIP top mounting plates using Blum's tool-free attachment system, enabling efficient installation and straightforward removal during fitting or adjustment.

Finished in **Onyx Black**, the hinge supports coordinated hardware specification in contemporary dark cabinetry schemes while maintaining full compatibility within the Blum hinge platform. The **Screw-On boss fixing** provides secure mechanical retention within the door and requires appropriate drilling preparation. Three-dimensional adjustment enables precise vertical, lateral and depth positioning to achieve accurate alignment and consistent door gaps.

---

### Product Features

- **95° opening angle** for controlled cabinet access
- Integrated **BLUMOTION soft-close mechanism**
- Designed for **half overlay door applications**
- **Screw-On boss fixing**
- Durable **Onyx Black finish**

- Compatible with Blum **CLIP top mounting plates**
- Three-dimensional adjustment capability

---

## Product Benefits

- Provides smooth and quiet door closing
- Supports efficient cabinet layouts using shared panels
- Suitable for installations with reduced opening clearance
- Ensures secure hinge retention with mechanical fixing
- Coordinates visually with contemporary dark cabinetry
- Suitable for residential and light commercial interiors

---

## Technical Characteristics

- Requires compatible Blum CLIP top mounting plates
- Screw-On boss requires correct drilling preparation
- Adjustable vertically, laterally and in depth
- Designed for integration within Blum cabinet systems
- Suitable for thicker or space-restricted door applications
- Correct hinge and mounting plate pairing ensures optimal performance

---

## Applications

This hinge is intended for half overlay cabinet door installations where a reduced opening angle is required due to cabinet configuration or spatial limitations. The integrated BLUMOTION soft-close mechanism ensures controlled and quiet closing performance, while the **Onyx Black finish** makes it particularly suitable for contemporary kitchens,

fitted furniture and dark cabinetry schemes in residential and light commercial interiors.

<b>Property</b>	<b>Value</b>
Finish	Onyx Black
Opening angle (°)	95
Application	Half Overlay
Boss	Screw-on
Closing Mechanism	Soft Close
Boss Drilling Depth (mm)	12.3
Max Door Thickness (mm)	32
Hinge Type	Profile Door