



Blum Clip Top Hinge – 95° Thick Door Inset BLUMOTION Sprung – Nickel – Inserta

Variant code: 71B9790-NI

Blum CLIP top BLUMOTION 95° Inset Hinge – Nickel is designed for cabinet doors requiring integrated soft-close performance within flush inset applications. Incorporating **BLUMOTION soft-close technology** within the hinge mechanism, it delivers smooth and controlled closing without the need for additional damping components, ensuring refined and consistent door movement.

With a **95° opening angle**, the hinge is particularly suited to inset installations where cabinet configuration or door thickness limits the use of wider opening hinges. Designed specifically for **inset cabinet doors**, it allows the door to sit flush within the cabinet frame, supporting clean architectural lines and precise reveals. The hinge clips securely onto compatible Blum CLIP top mounting plates using the tool-free attachment system, enabling efficient installation and straightforward removal during fitting or adjustment.

This hinge is available in both **Screw-on and Inserta boss fixing configurations**, providing flexibility across different installation methods and production environments. The Screw-on version offers traditional mechanical retention within the hinge cup and requires appropriate drilling preparation. The Inserta version incorporates integrated expansion dowels for rapid installation into pre-drilled hinge cup holes, reducing fitting time while maintaining secure anchoring. Manufactured from steel with a durable **nickel-plated finish**, the hinge offers a neutral appearance suitable for a wide range of cabinetry styles. Three-dimensional adjustment enables precise vertical, lateral and depth positioning to achieve accurate alignment and consistent door gaps.

Product Features

- **95° opening angle** for controlled inset access
- Integrated **BLUMOTION soft-close mechanism**

- Designed for **inset door applications**
- Available in **Screw-on and Inserta boss fixing options**
- Durable **nickel-plated steel finish**
- Compatible with Blum **CLIP top mounting plates**
- Tool-free clip-on hinge assembly
- Three-dimensional adjustment capability

Product Benefits

- Provides smooth and quiet door closing
- Supports flush inset cabinet aesthetics
- Offers installation flexibility for different manufacturing methods
- Ensures secure hinge retention
- Enables precise alignment and consistent reveals
- Suitable for installations with reduced opening clearance
- Appropriate for residential and light commercial interiors

Technical Characteristics

- Requires compatible Blum CLIP top mounting plates
- Screw-on version requires correct hinge cup drilling preparation
- Inserta version uses integrated expansion dowels for rapid installation
- Adjustable vertically, laterally and in depth
- Designed for integration within Blum cabinet systems
- Suitable for thicker or space-restricted inset applications

- Correct hinge and mounting plate pairing ensures optimal performance

Applications

This hinge is intended for inset cabinet door installations where a reduced opening angle is required due to cabinet configuration or door thickness. The integrated **BLUMOTION soft-close mechanism** ensures controlled and quiet closing performance, while the inset configuration supports clean, flush cabinet design. The availability of **Screw-on and Inserta fixing options** makes it suitable for both bespoke joinery and volume cabinet production in kitchens, bedrooms and fitted furniture across residential and light commercial interiors requiring durability, accurate alignment and enhanced user comfort.

Property	Value
Finish	Nickel
Opening angle (°)	95
Application	Inset
Boss	Inserta
Closing Mechanism	Soft Close
Boss Drilling Depth (mm)	12.3
Max Door Thickness (mm)	32
Hinge Type	Profile Door