



## Blum Clip Top Hinge – 95° Thick Door Overlay Unsprung – Nickel – Screw-on

Variant code: 70T9550.TL-NI

**Blum CLIP top Hinge – 95° Overlay Unsprung – Nickel** is designed for overlay cabinet door installations where controlled hinge movement is required without an integrated closing spring. As part of the **Blum CLIP top hinge system**, this hinge provides dependable operation and precise adjustment while allowing the door to move freely. The **unsprung hinge mechanism** makes it suitable for cabinetry using push-to-open mechanisms or external closing systems where hinge spring tension is not required.

The hinge features a **95° opening angle**, offering controlled access to cabinet interiors while maintaining stable hinge performance. Designed for **overlay cabinet door applications**, the final overlay position is determined by the selected mounting plate, allowing flexibility across different cabinet constructions and installation requirements.

The hinge clips securely onto compatible Blum mounting plates using the **tool-free CLIP top system**, enabling quick installation and straightforward removal during cabinet adjustment or maintenance. Integrated **three-dimensional adjustment** allows precise vertical, lateral and depth positioning to achieve accurate door alignment and consistent door gaps.

This variant uses **Screw-on boss fixing**, providing secure mechanical attachment within the cabinet door when installed into correctly prepared hinge cup drilling. The screw-on fixing method ensures strong retention within the door material and is widely used in both bespoke joinery and cabinet manufacturing environments. Manufactured from durable steel with a **nickel-plated finish**, the hinge offers corrosion resistance and a clean, neutral appearance suitable for most cabinet interiors.

---

### Product Features

- **95° opening angle** for controlled cabinet access
- **Unsprung hinge mechanism** allowing

free door movement

- Designed for **overlay cabinet door applications**
- **Screw-on boss fixing**
- Durable **nickel-plated steel finish**
- Part of the **Blum CLIP top hinge system**
- **Tool-free CLIP hinge attachment**
- **Three-dimensional adjustment capability**

---

## Product Benefits

- Suitable for cabinets using **push-to-open or external closing systems**
- Ensures secure hinge installation through **Screw-on boss fixing**
- Enables precise door alignment and consistent reveals
- Provides reliable hinge performance in everyday use
- Integrates seamlessly within the **Blum hinge platform**
- Suitable for residential and light commercial cabinetry

---

## Technical Characteristics

- Requires compatible **Blum CLIP top mounting plates**
- Designed for **overlay cabinet door construction**
- **Screw-on boss fixing requires correct hinge cup drilling preparation**
- Adjustable vertically, laterally and in depth
- Steel hinge construction with **nickel protective finish**
- Correct hinge and mounting plate pairing

ensures optimal door performance

---

## Applications

This hinge is intended for **overlay cabinet door installations** in kitchens, wardrobes, storage furniture and fitted cabinetry where free hinge movement is required. The **unsprung hinge design** allows the hinge to work with push-to-open mechanisms or external closing systems. The **Screw-on boss fixing** ensures secure hinge attachment within the cabinet door, making it suitable for both bespoke joinery projects and cabinet manufacturing environments requiring durability, precision and consistent door alignment.

Property	Value
Finish	Nickel
Opening angle (°)	95
Application	Overlay
Boss	Screw-on
Closing Mechanism	Unsprung
Boss Drilling Depth (mm)	12.3
Max Door Thickness (mm)	32
Hinge Type	Profile Door