



Blum Clip Top Mini Hinge – 94° Overlay Sprung – Nickel – Screw-on

Variant code: 71T0550

Blum CLIP top MINI Hinge – 94° Overlay Sprung – Nickel is engineered for compact cabinet applications where reduced hinge dimensions are required without compromising performance. As part of the Blum CLIP top MINI range, this hinge is specifically developed for cabinets with limited internal space while delivering dependable and consistent operation. The integrated **sprung mechanism** ensures reliable self-closing performance without the need for additional closing components.

With a **94° opening angle**, the hinge provides controlled access suited to compact cabinet constructions. Designed for **full overlay door applications**, it allows the cabinet door to fully cover the cabinet side panel, supporting clean exterior lines and efficient cabinet design. The hinge clips securely onto compatible Blum CLIP top mounting plates using the tool-free attachment system, enabling efficient installation and straightforward removal for adjustment or maintenance. Three-dimensional adjustment allows accurate vertical, lateral and depth positioning to achieve precise alignment and consistent door gaps.

The **Screw-on boss fixing** provides secure mechanical retention within the door and requires correct hinge cup drilling preparation. This traditional fixing method ensures dependable anchoring within standard cabinet door materials. Manufactured from durable nickel-plated steel, the hinge offers a neutral finish suitable for a wide range of cabinetry styles while maintaining full compatibility within the Blum hinge platform.

Product Features

- **94° opening angle** for controlled cabinet access
- Compact **CLIP top MINI design**
- Integrated **sprung mechanism** for self-closing action

- Designed for **full overlay door applications**
- **Screw-on boss fixing**
- Durable **nickel-plated steel finish**
- Compatible with Blum **CLIP top mounting plates**
- Three-dimensional adjustment capability

Product Benefits

- Provides reliable self-closing performance in compact cabinets
- Suitable for installations with restricted internal space
- Ensures secure hinge retention with mechanical fixing
- Supports clean full overlay cabinet aesthetics
- Enables precise alignment and consistent reveals
- Appropriate for residential and light commercial interiors

Technical Characteristics

- Requires compatible Blum CLIP top mounting plates
- Screw-on boss requires accurate hinge cup drilling preparation
- Adjustable vertically, laterally and in depth
- Designed for reduced cabinet depth applications
- Manufactured from steel with nickel-plated finish
- Correct hinge and mounting plate pairing ensures optimal performance

Applications

This hinge is intended for full overlay cabinet door installations in compact or reduced-depth cabinetry where space constraints limit the use of larger hinges. The **94° opening angle** provides controlled access while maintaining structural stability. The Screw-on fixing method ensures secure mechanical attachment, making it suitable for kitchens, bathroom furniture, storage units and bespoke joinery projects requiring reliable operation and precise alignment.

Property	Value
Finish	Nickel
Opening angle (°)	94
Application	Overlay
Boss	Screw-on
Closing Mechanism	Sprung
Boss Drilling Depth (mm)	12.5
Max Door Thickness (mm)	22
Hinge Type	Frame door