



DIN Bathroom Lock, 78mm c/c, 60mm b/s – Satin Stainless Steel – Radius Forends

Variant code: 2405.04R.SSS

The **DIN Bathroom Lock** is a high-performance mortice lock designed to provide secure privacy locking for bathroom and washroom doors in commercial, residential and public buildings. Featuring **78mm centres** and a **60mm backset**, this lock is engineered to DIN standards for smooth operation and dependable performance. Finished with a durable **Satin Stainless Steel (SSS)** forend, it complements contemporary architectural ironmongery while delivering long-lasting reliability.

Manufactured with a robust **90mm x 165mm case**, the lock features a **stainless steel latch bolt and deadbolt** for exceptional durability. It includes a **Grip Tight follower spring** for improved lever handle return, together with an **anti-rattle strike plate and dust box** for quieter operation and a professional installation. Available with **square or radius forend profiles**, every lock is factory quality-control tested, certified to **BS EN 12209:2003**, approved for **FD30 and FD60 timber fire doors**, **Certifire CF850** certified, **CE marked**, and backed by a **10-year mechanical guarantee**.

Ideal for commercial fit-outs, residential developments and refurbishment projects, the DIN Bathroom Lock delivers certified fire performance, reliable privacy locking and long-lasting durability for professional door installations.

Product Features

- DIN bathroom mortice lock
- 78mm lock centres
- 60mm backset
- Case size: 90mm x 165mm
- Forend dimensions: 235 x 22 x 3mm
- Stainless steel latch bolt and deadbolt
- Includes Grip Tight follower spring
- Supplied with anti-rattle strike plate and dust box
- Available with square or radius forend profiles
- Factory quality-control tested
- Tested to BS EN 12209:2003

- Suitable for FD30 & FD60 timber fire doors
- Certifire approved – CF850
- CE marked
- 10-year mechanical guarantee

Product Benefits

- **Provides secure privacy locking with smooth, reliable everyday operation**
- **Certified for use on FD30 and FD60 timber fire doors with BS EN 12209 and Certifire CF850 approval**
- **Grip Tight follower spring ensures excellent lever handle return and consistent performance**
- Stainless steel latch bolt and deadbolt provide long-lasting durability and corrosion resistance
- Anti-rattle strike plate reduces door closing noise
- Choice of square or radius forend suits different door preparations
- Factory tested and CE marked for assured quality and compliance
- Backed by a 10-year mechanical guarantee for long-term confidence

Technical Characteristics

- Product Type: DIN Bathroom Lock
- Lock Centres: 78mm
- Backset: 60mm
- Case Size: 90mm x 165mm
- Forend Size: 235 x 22 x 3mm
- Latch Bolt: Stainless Steel
- Deadbolt: Stainless Steel
- Finish: Satin Stainless Steel (SSS)
- Forend Profile: Square or Radius
- Includes: Grip Tight Follower Spring, Anti-Rattle Strike Plate & Dust Box
- Standard: BS EN 12209:2003
- Fire Rating: FD30 & FD60 Timber Doors
- Certification: Certifire CF850
- Compliance: CE Marked
- Guarantee: 10-Year Mechanical Guarantee

Applications

The **DIN Bathroom Lock** is ideal for **hotels, apartments, offices, hospitals, care homes, schools, leisure facilities and residential properties**. Designed for installation on **bathroom, WC, ensuite and washroom doors**, it provides dependable privacy locking when used with

compatible **DIN lever handles, bathroom turns and emergency release furniture**, while meeting the demands of high-traffic commercial and residential environments.

Property	Value
Finish	Satin Stainless Steel
Fire Rating	FD30 & FD60 Timber Doors
Certification	Certifire CF850
Standards Tested	BS EN 12209:2003
Case Size	90mm x 165mm
Backset (mm)	60
Forend Size (mm)	235 x 22 x 3mm
Lock Centre (mm)	78