SWS HARDWARE

Tel: 01626 333900
Email: info@swshardware.com



DIN Euro Profile Sash Lock Case, 72mm c/c, 60mm b/s - Satin Stainless Steel - Square Forends

Variant code: 2405.01.SSS

The **DIN Euro Profile Sash Lock Case** is a premium mortice lock designed for use with Euro profile cylinders in commercial, residential and public buildings. Featuring **72mm centres** and a **60mm backset**, this high-performance sash lock delivers secure locking, smooth operation and exceptional durability. Finished with a **Satin Stainless Steel (SSS)** forend, it provides a professional appearance that complements modern architectural door hardware.

Manufactured with a robust **90mm x 165mm case**, the lock features a **stainless steel latch bolt and deadbolt** for long-lasting performance and enhanced corrosion resistance. It incorporates a **Grip Tight follower spring** to ensure excellent lever handle return and is supplied complete with an **anti-rattle strike plate and dust box** for quieter operation and a professional installation. Available with **square or radius forend profiles**, every lock is factory quality-control tested, certified to **BS EN 12209:2003**, approved for **FD30 and FD60 timber fire doors**, **Certifire CF850** certified, **CE marked**, and backed by a **10-year mechanical guarantee**.

Suitable for commercial fit-outs, residential developments and refurbishment projects, the DIN Euro Profile Sash Lock Case provides dependable security, certified fire performance and long-term reliability for professional door installations.

Product Features

- DIN Euro profile sash lock case
- 72mm lock centres
- 60mm backset
- Case size: 90mm x 165mm
- Forend dimensions: 235 x 22 x 3mm
- Stainless steel latch bolt and deadbolt
- Includes Grip Tight follower spring
- Supplied with anti-rattle strike plate and dust box
- Available with square or radius forend profiles
- Factory quality-control tested

Tel: 01626 333900
Email: info@swshardware.com

- Tested to BS EN 12209:2003
- Suitable for FD30 & FD60 timber fire doors
- Certifire approved – CF850
- CE marked
- 10-year mechanical guarantee

Product Benefits

- **Provides secure locking for doors fitted with Euro profile cylinders**
- **Certified for FD30 and FD60 timber fire doors with BS EN 12209 and Certifire CF850 approval**
- **Grip Tight follower spring delivers smooth lever handle return and reliable long-term performance**
- Stainless steel latch bolt and deadbolt provide outstanding durability and corrosion resistance
- Anti-rattle strike plate reduces noise and improves door closing performance
- Available with square or radius forends to suit different door preparations
- Factory tested and CE marked for assured quality and compliance
- Supported by a 10-year mechanical guarantee for added peace of mind

Technical Characteristics

- Product Type: DIN Euro Profile Sash Lock Case
- Lock Centres: 72mm
- Backset: 60mm
- Case Size: 90mm x 165mm
- Forend Size: 235 x 22 x 3mm
- Latch Bolt: Stainless Steel
- Deadbolt: Stainless Steel
- Finish: Satin Stainless Steel (SSS)
- Forend Profile: Square or Radius
- Includes: Grip Tight Follower Spring, Anti-Rattle Strike Plate & Dust Box
- Compatible With: Euro Profile Cylinders
- Standard: BS EN 12209:2003
- Fire Rating: FD30 & FD60 Timber Doors
- Certification: Certifire CF850
- Compliance: CE Marked
- Guarantee: 10-Year Mechanical Guarantee

Applications

The **DIN Euro Profile Sash Lock Case** is ideal for **offices, schools, hospitals, hotels, apartment buildings, care homes, retail premises and**

SWS HARDWARE

Tel: 01626 333900
Email: info@swshardware.com

public buildings. Designed for installation on **timber internal and external doors** with compatible **Euro profile cylinders and lever handles**, it delivers reliable security, smooth operation and certified fire performance for medium and high-traffic commercial and residential applications.

Property	Value
Finish	Satin Stainless Steel
Fire Rating	FD30 & FD60 Timber Doors
Certification	Certifire CF850
Standards Tested	BS EN 12209 : 2003
Case Size	90mm x 165mm
Backset (mm)	60
Lock Centre (mm)	72