



DIN Mortice Latch, 60mm b/s – Satin Stainless Steel – Square Forends

Variant code: 2405.03.SSS

The **DIN Mortice Latch** is a high-performance architectural latch designed for smooth, reliable operation in commercial, residential and public buildings. Featuring a **60mm backset** and a premium **Satin Stainless Steel (SSS)** finish, this latch is manufactured to meet the demands of high-traffic environments while providing dependable everyday performance. Engineered to DIN standards, it is suitable for use with a wide range of lever handles and door furniture.

Manufactured with a **stainless steel latch bolt**, the latch incorporates a **Grip Tight follower spring** for improved handle return and consistent operation. Supplied complete with an **anti-rattle strike plate and dust box**, it delivers quieter closing and a professional installation. Available with **square or radius forend profiles**, every latch is factory quality-control tested and certified to **BS EN 12209:2003**, **Certifire CF850**, and is **FD30/FD60 timber door tested**. The latch is also **CE marked** and backed by a **10-year mechanical guarantee** for complete confidence.

Ideal for new-build developments, commercial fit-outs and refurbishment projects, the DIN Mortice Latch combines certified fire performance, exceptional durability and smooth operation, making it the professional choice for modern door installations.

Product Features

- DIN mortice latch with 60mm backset
- Case size: 90mm x 165mm
- Forend dimensions: 235 x 22 x 3mm
- Stainless steel latch bolt
- Includes Grip Tight follower spring
- Supplied with anti-rattle strike plate and dust box
- Available in square or radius forend profiles
- Factory quality-control tested
- Tested to BS EN 12209:2003
- FD30 & FD60 timber door tested
- Certifire approved – CF850
- CE marked

- 10-year mechanical guarantee

Product Benefits

- Provides smooth, reliable door latching for high-frequency use
- Certified for fire-rated timber doors with BS EN 12209 and Certifire CF850 approval
- Grip Tight follower spring ensures excellent lever handle return and long-term performance
- Anti-rattle strike reduces door noise during closing
- Stainless steel latch bolt offers excellent durability and corrosion resistance
- Choice of square or radius forend suits a variety of door preparations
- CE marked and factory tested for dependable quality
- Backed by a 10-year mechanical guarantee for added peace of mind

Technical Characteristics

- Product Type: DIN Mortice Latch
- Backset: 60mm
- Case Size: 90mm x 165mm
- Forend Size: 235 x 22 x 3mm
- Latch Bolt: Stainless Steel
- Finish: Satin Stainless Steel (SSS)
- Forend Profile: Square or Radius
- Includes: Grip Tight Follower Spring, Anti-Rattle Strike Plate & Dust Box
- Standard: BS EN 12209:2003
- Fire Rating: FD30 & FD60 Timber Doors
- Certification: Certifire CF850
- Compliance: CE Marked
- Guarantee: 10-Year Mechanical Guarantee

Applications

The **DIN Mortice Latch** is ideal for **offices, schools, hospitals, hotels, apartment buildings, care homes, retail premises and public buildings**. Designed for installation in **timber internal doors** with compatible lever handles, it is particularly suited to **fire-rated FD30 and FD60 door assemblies**, providing dependable latching performance and certified fire safety compliance in demanding commercial and residential environments.

Property	Value
Finish	Satin Stainless Steel
Fire Rating	FD30 / FD60 Timber Doors
Certification	Certifire CF850
Standards Tested	BS EN 12209:2003
Case Size	90mm x 165mm
Backset (mm)	60
Forend Size (mm)	235 x 22 x 3