SWS HARDWARE

Tel: 01626 333900
Email: info@swshardware.com



Double Action Floor Spring Non Hold Open EN3 inc Cover Plate & Accessories - Satin Stainless Steel

Variant code: 2825.02.SSS

Double Action Floor Spring is a high-performance floor-mounted door control designed to provide smooth, controlled operation for double action doors in demanding commercial environments. Finished in **satin stainless steel** and supplied complete with a **cover plate and installation accessories**, this **non hold open EN3 floor spring** is particularly suited to locations such as **hospitals, care homes, schools and public buildings**, where effortless door operation and long-term reliability are essential.

Featuring an advanced **cam and roller action mechanism**, the TS.7003NHO delivers a significantly smoother opening action than conventional floor springs, helping to improve accessibility while maintaining controlled closing performance. Suitable for doors weighing up to **105kg** and **950mm wide**, it incorporates adjustable **closing speed, latch speed and backcheck**, allowing the door operation to be precisely tailored for different applications.

Fire tested to **EN1634-1** and **CE marked**, the Rutland TS.7003NHO provides dependable, compliant performance for commercial door installations. Its durable construction and user-friendly operation make it an ideal solution where accessibility, safety and durability are key requirements.

Product Features

- Heavy-duty double action floor spring
- Non hold open model
- Supplied with cover plate and installation accessories
- Satin stainless steel finish
- Fixed EN3 power size
- Advanced cam and roller action mechanism
- Adjustable closing speed, latch speed and backcheck
- Suitable for doors up to 105kg and 950mm wide
- Fire tested to EN1634-1

Tel: 01626 333900
Email: info@swshardware.com

- CE marked

Product Benefits

- **Cam and roller mechanism provides smooth, low-effort door opening**
- **Ideal for healthcare and care environments where accessibility is essential**
- **Adjustable closing controls allow precise door operation**
- Backcheck helps protect doors and surrounding walls from impact damage
- Double action design allows doors to swing in both directions
- Heavy-duty construction delivers reliable long-term performance
- Fire-tested and CE marked for compliant commercial installations
- Complete kit supplied with cover plate and accessories for straightforward installation

Technical Characteristics

- Product Type: Double Action Floor Spring
- Model: Rutland TS.7003NHO
- Operation: Double Action
- Hold Open: Non Hold Open
- Power Size: Fixed EN3
- Maximum Door Weight: 105kg
- Maximum Door Width: 950mm
- Mechanism: Cam and Roller Action
- Adjustments: Closing Speed, Latch Speed & Backcheck
- Finish: Satin Stainless Steel
- Supplied With: Cover Plate and Installation Accessories
- Fire Rating: EN1634-1
- Certification: CE Marked

Applications

The **Rutland TS.7003NHO Double Action Floor Spring** is ideal for **hospitals, care homes, healthcare facilities, schools, universities, hotels, offices, retail premises and public buildings**. Designed for **double action commercial doors**, it provides smooth, controlled operation with low opening resistance, making it particularly suitable for environments where accessibility, safety and reliable door control are essential.

Property	Value

SWS HARDWARE

Tel: 01626 333900
Email: info@swshardware.com

Property	Value
Finish	Satin Stainless Steel
Fire Rating	EN1634-1
Max Door Width (mm)	950
Max Door Weight (kg)	105
Power Size	Fixed EN3
Certification	CE Marked
Mechanism	Cam and Roller Action
Adjustments	Closing Speed, Latch Speed & Backcheck