



## Hawa Junior 160 B – Set for 1 Panel – Without Track

**Variant code: 11695**

Fitting for top-running wooden doors up to 160 kg (352 lbs.), with surface mounted running track or running track flush with the ceiling. Ceiling mounting. Minimal installation height.

**Aesthetics** – Low installation height, only minimal gap between door and running track.

**Productivity** – Interlocking of the suspension at the front edge is possible.

Set comprises of:

- 2x Two-wheeled trolley, plastic wheels, hanger bolt M14 (Junior 160 B G GV)
- 1x Track stop, adjustable retaining force
- 2x Top fixed suspension with plate M14 (type Junior 160 B)
- 2x Cover cap for suspension profile, plastic anthracite-grey RAL 7016
- 1x Floor guide, screw mounting, rattle proof, groove width 14 mm, plastic
- 1x Screw-on rubber door stop 29 mm

| Property                | Value                                       |
|-------------------------|---|
| Min Door Thickness (mm) | 35  |
| Max Weight (kg)         | 160   |
| Max Height (mm)         | 4000  |
| Max Width (mm)          | 3000  |
| Max Door Thickness (mm) | 80  |
| Mounting Position       | Ceiling mounting, Ceiling mounting recessed |
| Running Position        | Top Running                                 |

## A collection of various mechanical components including pulleys, rollers, brackets, and fasteners. The items are arranged in a collage-like fashion. At the top left, there are two white pulleys mounted on a metal frame. Below them are two more white pulleys. To the right of these is a vertical metal bracket with a horizontal slot and a bolt. In the center, there are two blue metal brackets with slots and two blue metal bolts. At the bottom left, there is a black rectangular component with a metal bracket. At the bottom center, there are two blue metal brackets with slots. At the bottom right, there is a black circular component.

