



Hawa Concepta 25 – Sliding Door Hardware – Set for 1 Door – 1250mm–1850mm

Variant code: 27648

Hawa Concepta 25 – Single Door Pivot/Slide-in System (1250mm–1850mm)

Experience the future of space design with the **Hawa Concepta 25**, the innovative hardware solution for pivoting and laterally sliding a single wooden door into a concealed recess or "pocket." This set, specifically engineered for doors with a height between **1250mm and 1850mm**, transforms conventional spaces, offering seamless functionality and minimalist aesthetics.

Imagine an office hidden inside a living room cabinet, a tucked-away laundry unit, or a seamlessly integrated kitchen appliance station. The Concepta 25 makes these multi-functional designs a reality by allowing the door to first pivot outwards, then glide smoothly to the side and completely disappear, providing **unobstructed access** to the entire cabinet interior.

Key Product Highlights

Design & Space Optimisation

- **Flush Integration:** When closed, the door sits perfectly **flush** with the adjacent cabinet fronts, maintaining a clean, uniform, and modern aesthetic.
- **Total Concealment:** The door pivots 90° and slides fully into a narrow recess (pocket), freeing up valuable floor space and removing the visual clutter of open doors.
- **Floor-to-Ceiling Solutions:** The smart design **omits the need for a bottom guide channel** across the floor, making it ideal for room-high cabinets, walk-in closets, or concealing wall recesses without interrupting the flooring.

Performance & Comfort

- **Maximum Door Specs:** This set is designed for wooden doors with a height of **1250mm to 1850mm** and a maximum

weight of **25 kg (55 lbs)**.

- *Door Width*: 300mm to 750mm.
- *Door Thickness*: 19mm to 50mm
(Check door weight/height ratio for precise suitability).
- **Smooth Motion**: The unique **Hawa scissor technology** ensures the door pivots and slides with an even, smooth, and effortless movement, preventing jamming.
- **Soft Closing Mechanism**: Integrated soft closing and dampening systems provide a high degree of movement comfort, ensuring the door glides quietly and gently to its final open or closed position.

Installation & Flexibility

- **Simplified Installation**: All components are designed to be screwed onto an **intermediate panel** and are adjustable **from the front**, eliminating the need for awkward access panels and simplifying the fitting process.
- **Universal Handing**: The same set can typically be used for both **left-hand** and **right-hand** side applications (always check product documentation for final confirmation).
- **Comprehensive Set**: This product is a complete set of fixtures and fittings required for the pivot and lateral slide-in motion of one single door within the specified height range.

Note: The exact components included will be tailored for the specified door height range (1250mm–1850mm). We recommend consulting the official Hawa mounting instructions and planning tools for precise cabinet dimensions and installation details.

Property	Value
Min Door Thickness (mm)	19
Max Weight (kg)	25
Max Height (mm)	1850
Max Width (mm)	750
Max Door Thickness (mm)	50

Property**Value**

Running Position

Fully opening Inslide, Mixslide, Forslide

Gallery

