

Hawa Concepta 30, Set for 1 Door – 1851 – 2300mm

Variant code: 27649

The Hawa Concepta 25 set comprises of all fixtures and fittings for pivoting and lateral sliding in wooden doors up to 30kg (66lbs)

Enables multi-functional room design, paired with a flush-fitting.

Set comprises of:

- 1x Upright 2300 mm (7'6 9/16"), alu plain anodized
- 2x Upright guide, rattle proof with plastic rollers
- 1x torsion plate
- 1x Scissor action, complete, 1500 mm (4'11 1/16"), galvanized steel, Hawa Concepta 30
- 1x Front scissor guide, alu plain anodized
- 1x Rear scissor guide, alu plain anodized
- 1x Rear scissor bearing, 55 mm (2 5/32") galvanized steel
- 1x Concealed hinge with damper, nickel-plated, 3 pieces
- 1x Set of screws for concealed hinges 4x16 mm (5/8"), 10 pieces
- 1x Spacer profile 860 mm (2'9 27/32"), pre-drilled, plastic black
- 1x Set of screws for spacer profile, 7 pieces PH 4x16 mm (5/8")
- 1x Brush guide, set of 3 pieces, plastic black
- 1x Stop cover cap Concepta, depth adjustable, top left/bottom right
- 1x Stop cover cap, Concepta depth adjustable, top right/bottom left
- 1x Cover plates, stainless steel (1 pair)
- 2x Bottom guide channel 896 mm (2'11 9/32"), alu plain anodized, predrilled
- 1x Stop damper with retaining bracket for Hawa Concepta 30 40 50
- 1x Door retractor 30 40 with damper, plastic black
- 1x Soft closing system for end position and cover caps, plastic black
- 1x Screw set for fitting hardware to cabinet body 4,5x20 mm (25/32"), 22 pieces
- 1x Hex key, 3 mm (1/8"), with handle
- 1x Installation aid, plastic, red

Not sure which Hawa Concepta is right for your project? Use the Hawa Planning Tool below to help you decide:

<https://concepta.hawa.com/>

Property	Value
Running Position	Fully opening Inslide, Mixslide, Forslide
Minimum Door Thickness (mm)	19
Maximum Door Thickness (mm)	50
Max Width (mm)	900
Max Weight (kg)	30
Max Height (mm)	2300

Gallery

