



Hawa Concepta 50, Set for 1 Door - 2301 - 2760mm

Variant code: 27651

The Hawa Concepta 50 comprises of all fixtures and fittings for pivoting and lateral sliding in wooden doors up to 50kg (110 lbs).

Enables multi-functional room design, paired with a flush-fitting design.

Set comprises of:

- 1x Upright 2760 mm (9' 21/32"), alu plain anodized
- 1x Two-wheeled running gear, heightadjustable, with torsion plate, zinc-plated matt
- 1x Upright guide, rattle proof with plastic rollers
- 1x Scissor action, complete, 1500 mm (4'11 1/16"), galvanized steel
- 1x Front scissor guide, alu plain anodized 490mm
- 1x Rear scissor guide, alu plain anodized cut to size
- 1x Concealed hinge with damper, nickelplated, 5 pieces
- 1x Set of screws for concealed hinges 4x16 mm (5/8"), 10 pieces
- 1x Spacer profile 860 mm (2'9 27/32"), predrilled, plastic black
- 1x Set of screws for spacer profile, 7 pieces PH 4x16 mm (5/8")
- 1x Brush guide, set of 3 pieces, plastic black
- 1x Top track 896 mm (2'11 9/32"), alu plain anodized, pre- drilled
- 1x Bottom guide channel 896 mm (2'11 9/32"), alu plain anodized, predrilled
- 1x Stop damper with retaining bracket for Hawa Concepta 30 40 50
- 1x Door retractor 25 50 with damper, plastic black
- 1x Stop cover cap Concepta, depth adjustable, top left/bottom right
- 1x Stop cover cap,Concepta depth adjustable, top right/bottom left
- 1x Pair Cover plates, stainless steel
- 1x Soft closing system for end position and cover caps, plastic black
- 1x Screw set for fitting hardware to cabinet body 4,5x20 mm (25/32"), 22



pieces

- 1x Hex key, 3 mm (1/8"), with handle
- 1x Installation aid, plastic, red

Not sure which Hawa Concepta is right for your project? Use the Hawa Planning Tool below to help you decide:

https://concepta.hawa.com/

Property	Value
Running Position	Fully opening Inslide, Mixslide, Forslide
Min Door Thickness (mm)	19
Max Door Thickness (mm)	50
Max Width (mm)	900
Max Weight (kg)	50
Max Height (mm)	2850



Gallery



