



Hawa Porta 100 HMT Pocket – Push-to-open – Set for 1 Door – With 2000mm Running Track

Variant code: 057.3181.072

Fitting for top-running wooden doors up to 100 kg (220 lbs.), with surface mounted running track or running track flush with the ceiling. Optionally with soft and self closing mechanism.

Wall pocket solution.

Set comprises:

- 2x Runner Hawa Porta 100, ball bearings, rollers plastic, white
- 2x Stopper Hawa Porta 60/100, without retention spring, plastic grey
- 1x Damper Hawa Soft Close Building, top running, plastic
- 1x Trigger Hawa Soft Close Building, zinc diecasting
- 1x Push to Open Hawa Porta 100, with self-closing
- 1x Release piece Hawa Porta 100, zinc die casting
- 2x Screw set Hawa Soft Close Building
- 1x Slotted hexagon head screw M8x36 mm, steel, zinc plated
- 1x Hexagon socket head cap screw M8x35 mm, steel, zinc coated
- 1x Cover cap, plastic, grey
- 1x Running gear holder Hawa Porta 60/100 HM, plastic, anthracite
- 1x Running gear holder Hawa Porta 60/100 HMT, plastic, anthracite
- 1x Housing Hawa Porta 60/100 HM, steel, zinc plated
- 1x Housing Hawa Porta 60/100 HM, steel, zinc plated, niche
- 8x Flat countersunk head chipboard screw 4x40 mm, steel, zinc plated
- 1x Bottom guide with roller, adjustable, plastic, anthracite
- 4x Flat countersunk head chipboard screw 4x20 mm, steel, zinc plated
- 1x Running track Hawa Porta 60/100, aluminium, anodized, pre-drilled, L= 2000 mm
- 9x Assembly pin, plastic, grey
- 10x Cross recessed flat countersunk head



wood screw 5x40 mm, steel, zinc plated

| Property | Value |
|-------------------------|--|
| Min Door Thickness (mm) | 30 |
| Max Weight (kg) | 100 |
| Max Height (mm) | 2700 |
| Max Width (mm) | 1600 |
| Max Door Thickness (mm) | 80 |
| Mounting Position | Ceiling mounting and ceiling mounting recessed |
| Running Position | Top Running |



Gallery

