



Blum Clip Top Hinge – 95° Aluminum Door Overlay Sprung – Onyx Black

Variant code: 71T950A-OB

Blum CLIP top – 95° Overlay Sprung Hinge – Onyx Black is designed to provide reliable and consistent self-closing performance in overlay cabinet applications where a reduced opening angle is required. Incorporating an integrated **sprung mechanism**, the hinge delivers controlled door movement without the need for additional closing components. The 95° opening angle makes it particularly suitable for installations where cabinet configuration or door thickness restricts the use of wider opening hinges.

Designed for **overlay cabinet doors**, the final overlay dimension is determined by mounting plate selection, allowing flexibility across a range of cabinet constructions. As part of the Blum CLIP top system, the hinge clips securely onto compatible mounting plates using a tool-free attachment method, enabling efficient installation and straightforward adjustment. Three-dimensional adjustment allows precise vertical, lateral and depth positioning to achieve accurate alignment and consistent door gaps.

Finished in durable **Onyx Black**, the hinge supports coordinated hardware specification in contemporary dark cabinetry schemes. Manufactured to Blum's engineering standards, it integrates seamlessly within the wider CLIP top platform while offering dependable performance in everyday use.

Product Features

- **95° opening angle** for controlled cabinet access
- Integrated **sprung mechanism** for self-closing action
- Designed for **overlay door applications**
- Durable **Onyx Black finish**
- Compatible with Blum **CLIP top mounting plates**

- Tool-free clip-on hinge assembly
- Three-dimensional adjustment capability
- Concealed hinge construction

Product Benefits

- Provides reliable and consistent self-closing performance
- Supports clean overlay cabinet aesthetics
- Enables precise alignment and even door gaps
- Coordinates visually with contemporary dark cabinetry
- Suitable for installations with reduced opening clearance
- Appropriate for residential and light commercial interiors

Technical Characteristics

- Requires compatible Blum CLIP top mounting plates
- Adjustable vertically, laterally and in depth
- Designed for integration within Blum cabinet systems
- Suitable for standard overlay cabinet constructions
- Engineered for long-term durability and consistent operation
- Correct hinge and mounting plate pairing ensures optimal performance

Applications

This hinge is intended for overlay cabinet door installations where a reduced opening angle is required due to cabinet layout or spatial constraints. The integrated **sprung mechanism** ensures dependable closing performance, while

the **Onyx Black finish** makes it particularly suitable for contemporary kitchens, fitted furniture and dark cabinetry schemes. It is commonly specified in residential and light commercial interiors requiring durability, precise alignment and consistent hinge operation.

| Property | Value |
|-------------------------|----------------|
| Finish | Onyx Black |
| Opening angle (°) | 95 |
| Application | Overlay |
| Closing Mechanism | Sprung |
| Max Door Thickness (mm) | 24 |
| Type | Aluminum Frame |