SWS HARDWARE
Tel: 01626 333900
Email: info@swshardware.com



Acoustic - Fire & Smoke Seal (15mm W x 4mm D x 3000mm L) - Dark Brown

Variant code: LP1504.AS.3000.DB

Acoustic - Fire & Smoke Seal (15mm x 4mm x 3000mm) - Dark Brown

Product Overview

Upgrade your door's performance with our **Acoustic - Fire & Smoke Seal** in a rich dark brown finish. . This self-adhesive, multi-purpose seal is engineered to provide superior protection against noise, smoke, and fire, ensuring the safety and comfort of any space. Perfect for both residential and commercial applications, this easy-to-install seal helps meet building regulations and enhances a door's overall functionality. Its compact design (15mm W x 4mm D) and generous length (3000mm) make it suitable for a variety of door frames, including those with intricate profiles.

Key Features & Benefits

- **Certified Protection:** Independently tested to provide up to 60 minutes of fire resistance (FD60 rating) and effectively block the passage of cold smoke. This dual-action capability is crucial for fire safety compliance and is a key feature in both new builds and renovation projects.
- **Superior Soundproofing:** The high-density polymer material significantly reduces noise transmission, creating a quieter, more peaceful environment. This is an excellent solution for bedrooms, offices, or any area where acoustic privacy is desired.
- **Smoke & Draft Sealing:** The seal creates a tight barrier that prevents the spread of cold smoke and minimises drafts, leading to improved energy efficiency and lower heating costs. This feature also helps to prevent the movement of dust and allergens, contributing to a cleaner indoor air quality.
- **Easy, Self-Adhesive Installation:** Featuring a strong, self-adhesive backing,

Tel: 01626 333900
Email: info@swshardware.com

this seal can be quickly and securely applied to most door frames without the need for screws or nails. Simply cut to the required length and press into place.

- **Aesthetic & Durable:** The elegant dark brown finish blends seamlessly with most dark wood doors and frames. Made from a durable, flexible polymer, the seal is designed to withstand daily use without cracking or losing its effectiveness over time.

Ideal For

- **Residential Doors:** Bedrooms, home offices, and internal connecting doors.
- **Commercial Buildings:** Office doors, hotel rooms, and partition doors.
- **Safety Compliance:** Meeting building regulations for fire doors (FD30/FD60).

Technical Specifications

- **Dimensions:** 15mm (W) x 4mm (D) x 3000mm (L)
- **Colour:** Dark Brown
- **Material:** High-density, intumescent polymer
- **Fire Rating:** Up to 60 minutes (FD60)
- **Adhesive:** Self-adhesive backing
- **Application:** Door frames, door stops, and rebates