



Salice Pacta – Compact Push to open Flap Hinge with Mounting Plates (Power rating I)

Variant code: FRBKFEPI9N9

Salice Pacta: The Ultimate Compact Push-to-Open Flap Hinge (Power Rating I)

Salice Pacta, a revolutionary compact hinge system specifically engineered for downward-opening flap doors. Unlike traditional systems that rely on bulky gas struts or intrusive cables, the Salice Pacta offers a clean, streamlined aesthetic with high-performance mechanics hidden within a sleek profile.

The **Power Rating I (Medium Strength)** is the versatile "sweet spot" of the range, optimised for medium-sized doors. It delivers a controlled, decelerated opening motion – the signature **S-move** action – that ensures your cabinet doors glide down smoothly without slamming.

Key Features & Benefits

- **Minimalist "Push-to-Open" System:** Perfect for modern, handle-less furniture. A simple touch on the door front triggers the mechanism for effortless access.
- **Flush Surface Integration:** When fully open, the door lies perfectly horizontal and flush with the cabinet base, creating an extended, continuous work surface or writing desk.
- **Space-Saving Design:** No external stays, pistons, or cables are required, leaving the interior of your cabinet completely unobstructed.
- **Integrated Smove Deceleration:** Features a built-in damper that controls the descent of the flap, protecting hinges and cabinetry from impact.
- **Total Adjustability:** Easily fine-tune your door alignment with 3D adjustment:

- **Side adjustment:** -1.5 mm to +1.5 mm
- **Height adjustment:** -1.5 mm to +1.5 mm
- **Depth adjustment:** -0.5 mm to +2.8 mm

Technical Specifications

- **Power Rating:** I (Medium Strength) — Ideal for door weights approx. **3.5kg to 6.5kg**.
- **Door Height Range:** Optimised for doors between **280mm and 400mm**.
- **Opening Angle:** 90° fixed.
- **Drilling Requirements:** Standard 35mm cup drilling, 13 mm deep.
- **Mounting:** Includes longitudinal snap-on mounting plates for a tool-free, secure connection to the cabinet base.
- **Durability:** Certified to **UNI EN 15828:2010 Level 3**, ensuring long-term reliability under vertical loads

FAQ: Salice Pacta vs. Standard Flap Stays

Feature	Salice Pacta Compact Hinge	Standard Flap Stay (Gas Strut/Cable)
Aesthetics	Completely hidden and ultra-compact.	Bulky hardware visible inside the cabinet.
Surface Alignment	Door opens perfectly flush with the base.	Often has a lip or gap between door and base.
Functionality	Hinge and stay are a single integrated unit.	Requires separate hinges plus a stay/strut.
Usable Space	Maximum; no cables or arms to snag items.	Limited; hardware occupies side-wall space.
Installation	Single drilling pattern; snap-on plates.	Multi-part installation; complex alignment.



Q: Do I need a central hinge? A: For cabinets wider than 900mm (35"), we strongly recommend adding a Salice Pacta Central Hinge to ensure stability and prevent door bowing.

Q: Is it suitable for heavy doors? A: The Power Rating I is for medium doors (3.5 – 6.5kg). If your door is heavier (up to 9.5kg), you should opt for the **Power Rating S** (Heavy) version.

Q: Can I use this for upward-opening doors? A: No, the Pacta is specifically designed for **downward (fall) flaps** only. For upward-opening doors, we recommend the Salice Wind or Lift systems.